



PDP-TELEVISION

Chassis : D74B(P_Europe_42HD)_Mustang
Model : PS42C7HDX/XET

SERVICE *Manual*

PDP-TELEVISION



PS-42C7HD

FEATURES

- DTV Built-In PDP TV
- Supreme Picture Quality
Supreme Convenience Quality
- RF, HDMI, 2 Scart, PC (Analog),
Component, Video, S-Video
- Slim line design
- Energy Saving



This Service Manual is a property of Samsung Electronics Co., Ltd.
Any unauthorized use of Manual can be punished under applicable
International and/or domestic law.

© Samsung Electronics Co., Ltd. **Feb. 2007**
Printed in Korea
AA82-04328A

Table of Contents

Chapter 1 Precaution

■ 1-1 Safety Precautions	1-1
■ 1-2 Servicing Precautions	1-3
■ 1-3 Static Electricity Precautions	1-4
■ 1-4 Installation Precautions	1-5

Chapter 2 Product Specification

■ 2-1 Product Features	2-1
■ 2-2 Key Features	2-2
■ 2-3 Specifications Analysis	2-6
■ 2-4 Accessories	2-7

Chapter 3 Alignment & Adjustment

■ 3-1 Service Instruction	3-1
■ 3-2 How to Access Service Mode	3-2
■ 3-3 Factory Data	3-3
■ 3-4 Service Adjustment	3-8
■ 3-5 Software Upgrade	3-11
■ 3-6 Replacements & Calibration	3-13

Chapter 4 Exploded View & Part List

■ 4-1 PS42C7HDX/XET	4-1
---------------------------	-----

Chapter 5 Electrical Part List

■ 5-1 PS42C7HDX/XET Service Item	5-1
--	-----

Chapter 6 Troubleshooting

■ 6-1 First Checklist for Troubleshooting	6-1
■ 6-2 Checkpoints by Error Mode	6-2
■ 6-3 Troubleshooting Procedures by ASS'Y	6-13

Chapter 7 Block Diagram

■ 7-1 Overall Block Diagram	7-1
■ 7-2 Partial Block Diagram	7-3

Chapter 8 Wiring Diagram

■ 8-1 Overall Wiring	8-1
■ 8-2 Partial Wiring	8-2

Chapter 9 PCB Diagram

■ 9-1 MAIN & DTV MODULE Board	9-1
■ 9-2 Power & IR Board	9-4
■ 9-3 Function Board	9-4
■ 9-4 Side AV Board	9-4
■ 9-5 Main SMPS Board	9-5
■ 9-6 DC-DC SMPS Board	9-6
■ 9-7 PDP Module	9-7

Chapter 10 Schematic Diagram

■ 10-1 Analog	10-1
■ 10-2 Digital	10-12

Chapter 11 Operation Instruction & Installation

■ 11-1 Product Features and Functions	11-1
■ 11-2 Installation Notes and Precautions	11-4

Chapter 12 Disassembly & Reassembly

■ 12-1 Overhaul Disassembly & Reassembly	12-1
--	------

Chapter 13 Circuit Description

■ 13-1 Power ON/OFF Signal Timing Sequence	13-1
■ 13-2 Partial Block Description	13-2

Chapter 14 Reference Information

■ 14-1 Other issues related to other products	14-1
■ 14-2 Technical Terms	14-3

1. Precaution

To avoid possible damages or electric shocks or exposure to radiation, follow the instructions below with regard to safety, installation, service and ESD.

1-1 Safety Precautions

1. Make sure all protective devices are properly installed including non-metallic handles and compartment covers when installing or re-installing the chassis or chassis assemblies.
2. Make sure that no gaps exist between the cabinets for children to insert their fingers in to prevent children from receiving electric shocks. Gaps mentioned above include ventilation holes of a too great magnitude between the PDP module and the cabinet mask, and the improper installation of the rear cabinet.

Errors may occur when the resistance is below 1.0 M Ω or over 5.2 M Ω .

In these cases, make sure that the device is repaired before sending it back to the customer.

3. Check for Electricity Leakage (Figure 1-1)
Warning: Do not use an insulated transformer for checking the leakage. Use only those current leakage testers or mirroring systems that comply with ANSIC 101.1 and the Underwriter Laboratory's specifications (UL1410, 59.7).






Fig. 1-1 AC Leakage Test

4. A high voltage is maintained within the specified limits using safety parts, calibration and tolerances. When voltage exceeds the specified limits, check each special part.
5. Warning for Engineering Changes:
Never make any changes or additions to the circuit design or the internal part for this product.
Ex: Do not add any audio or video accessory connectors. This might cause physical damage.
Furthermore, any changes or additions to the original design/engineering will invalidate the warranty.
6. Warning - Hot Chassis:
Some TV chassis are directly connected to one end of the AC power cord for electrical reasons.
Without insulated transformers, the product can only be repaired safely when the chassis is connected to the earthed end of the AC power source.

To make sure the AC power cord is properly connected, follow the instructions below. Use the voltmeter to measure the voltage between the chassis and the earthed ground. If the measurement is over 1.0V, unplug the AC power cord and change the polarity before re-inserting it. Measure the voltage between the chassis and the ground again.
7. Some TV chassis are shipped with an additional secondary grounding system. The secondary system is adjacent to the AC power line. These two grounding systems are separated in the circuit using an unbreakable/unchangeable insulation material.
8. When any parts, material or wiring appear overheated or damaged, replace them with new regular ones immediately. When any damage or overheating is detected, correct this immediately and make a regular check of possible errors.
9. Check for the original shape of the lead, especially that of the antenna wiring, any sharp edges, the AC power and the high voltage power. Carefully check if the wiring is too tight, incorrectly placed or loose. Never change the space between the part and the printed circuit board. Check the AC power cord for possible damages. Keep the part or the lead away from any heat-emitting materials.

10. Safety Indication:

Some electrical circuits or device related materials require special attention to their safety features, which cannot be viewed by the naked eye. If an original part is replaced with another irregular one, the safety or protective features will be lost even if the new one has a higher voltage or more watts.

Critical safety parts should be bracketed with ( ).
Use only regular parts for replacements (in particular, flame resistance and dielectric strength specifications).
Irregular parts or materials may cause electric shock or fire.

1-2 Servicing Precautions

Warning 1: First carefully read the "Safety Instruction" in this service manual.

When there is a conflict between the service and the safety instructions, follow the safety instruction at all times.

Warning 2: Any electrolytic capacitor with the wrong polarity will explode.

1. The service instructions are printed on the cabinet, and should be followed by any service personnel.
2. Make sure to unplug the AC power cord from the power source before starting any repairs.
 - (a) Remove or re-install parts or assemblies.
 - (b) Disconnect the electric plug or connector, if any.
 - (c) Connect the test part in parallel with the electrolytic capacitor.
3. Some parts are placed at a higher position than the printed board. Insulated tubes or tapes are used for this purpose. The internal wiring is clamped using buckles to avoid contact with heat emitting parts. These parts are installed back to their original position.
4. After the repair, make sure to check if the screws, parts or cables are properly installed. Make sure no damage is caused to the repaired part and its surroundings.
5. Check for insulation between the blade of the AC plug and that of any conductive materials (i.e. the metal panel, input terminal, earphone jack, etc).
6. Insulation Check Process: Unplug the power cord from the AC source and turn the switch on. Connect the insulating resistance meter (500v) to the AC plug blade.
7. Any B+ interlock should not be damaged.
If the metal heat sink is not properly installed, no connection to the AC power should be made.
8. Make sure the grounding lead of the tester is connected to the chassis ground before connecting to the positive lead. The ground lead of the tester should be removed last.
9. Beware of risks of any current leakage coming into contact with the high-capacity capacitor.
10. The sharp edges of the metal material may cause physical damage, so ensure wearing protective gloves during the repair.
11. Due to the nature of plasma display panels, partial after-images may appear if a still picture is displayed on the screen for a long period of time.
This is caused by brightness deterioration due to the storage effect of the panel, and to prevent this from happening, we recommend that the brightness and contrast are reduced.
(e.g.) Contrast: 25, Brightness: 50

The insulating resistance between the blade of the AC plug and that of the conductive material should be more than 1 MΩ.

1-3 Static Electricity Precautions


1. Some semi-conductive ("solid state") devices are vulnerable to static electricity. These devices are known as ESD. ESD includes the integrated circuit and the field effect transistor. To avoid any materials damage from electrostatic shock, follow the instructions described below.
2. Remove any static electricity from your body by connecting the earth ground before handling any semi-conductive parts or ass'ys. Alternatively, wear a dischargeable wrist-belt.
(Make sure to remove any static electricity before connecting the power source - this is a safety instruction for avoiding electric shock)
3. Remove the ESD ass'y and place it on a conductive surface such as aluminum foil to prevent accumulating static electricity.
4. Do not use any Freon-based chemicals.
Such chemicals will generate static electricity that causes damage to the ESD.
5. Use only grounded-tip irons for soldering purposes.
6. Use only anti-static solder removal devices.
Most solder removal devices do not support an anti-static feature. A solder removal device without an anti-static feature can store enough static electricity to cause damage to the ESD.
7. Do not remove the ESD from the protective box until the replacement is ready. Most ESD replacements are covered with lead, which will cause a short to the entire unit due to the conductive foam, aluminum foil or other conductive materials.
8. Remove the protective material from the ESD replacement lead immediately after connecting it to the chassis or circuit ass'y.
9. Take extreme caution in handling any uncovered ESD replacements. Actions such as brushing clothes or lifting your leg from the carpet floor can generate enough static electricity to damage the ESD.

CAUTION

These servicing instructions are for use by qualified service personnel only.
To reduce the risk of electric shock do not perform any servicing other than that contained in the operating instructions unless you are qualified to do so.

1-4 Installation Precautions

1. For safety reasons, more than two people are required for carrying the product.



2. Keep the power cord away from any heat emitting devices, as a melted covering may cause fire or electric shock.
3. Do not place the product in areas with poor ventilation such as a bookshelf or closet. The increased internal temperature may cause fire.
4. Bend the external antenna cable when connecting it to the product. This is a measure to protect it from being exposed to moisture. Otherwise, it may cause a fire or electric shock.
5. Make sure to turn the power off and unplug the power cord from the outlet before repositioning the product. Also check the antenna cable or the external connectors if they are fully unplugged. Damage to the cord may cause fire or electric shock.
6. Keep the antenna far away from any high-voltage cables and install it firmly. Contact with the high-voltage cable or the antenna falling over may cause fire or electric shock.
7. When connecting the RF antenna, check for a DTV receiving system and install a separate DTV reception antenna for areas with no DTV signal.
8. When installing the product, leave enough space (4") between the product and the wall for ventilation purposes.
A rise in temperature within the product may cause fire.
9. When moving a PDP with removable speakers, detach the speakers first before moving the main body. Moving the PDP main body without separating the speakers may cause the speakers to detach, possibly causing damage or injury.

MEMO

2. Product Specification

2-1 Product Features

Block	Specification	Major IC	Remark
RF	Tuner	DNOS403ZH261B(S)	SEMCO
Power	Input Voltage : AC 220 - 240 V~, 50 Hz		
Video	Scaler	SVP-PX	TRIDENT
	Video Decoder		
Sound	Sound Processor	STV8257DSX	ST Microelectronics
	Sound AMP	STA323W	ST Microelectronics
	Audio S/W	MM74HC4052	
PDP Module	Samsung SDI V5.1	42"HD	SAMSUNG SDI
Remocon	TM87B		
Cabinet	C7		

■ Chip Description

- SVP-PX (IC611) : SVPTMPX contains dual-purposed triple 10-bit high-precision and high speed video ADCs for both PC and video inputs, the high speed HDMI could support all HDMI inputs up to 135MHz with HDCP format, the high-performance multi-format 3D digital comb video decoder that supports NTSC, PAL, and SECAM*, a HDTV sync separator, motion adaptive de-interlacing engine, and the video format conversion engine, supporting multi-window display in many different output modes.
- STV8257DSX (IC503) : Digital Audio Decoder/Processor
- STA323W (IC505) : Audio power amplifiers

2-2 Key Features

Model	PS-42C7HD
Screen Size	107 Cm / 42 Inches (16:9)
Dimensions	1055(W) x 340(D) x 758.5(H) mm
Weight	39.5 Kg
Voltage	EU : AC 220-240V~, 50Hz CIS : AC 100-240V~, 50/60Hz
Colour System	PAL, SECAM, NT3.58, NT4.43
Sound System	BG, DK, I, L
Number of Pixels	1024(H) x 768(V)
ANTENNA input	VHF, UHF (75Ω unbalanced)
VIDEO input	SCART1, SCART2 AV (Side), S-VIDEO (Side) COMPONENT IN (480i/P, 576i/P, 720P, 1080i) PC IN (MINI D-SUB 15P) HDMI/DVI IN
AUDIO input	SCART1, SCART2 AV (Side), S-VIDEO (Side) Component PC DVI
Audio Output	AUDIO OUT Headphone (Side)
Speaker Output	10W + 10W (8Ω) (Headphone Out : 10 mW MAX)

■ H/W Configuration

- Video : SVP-PX
- Sound : STA8257DSX, STA323W
- Tuner : DNOS403ZH261B (S)

■ S/W Configuration

- Main Micom : M30840SGP (IC202)
- Sub Micom : 3F866BXZZ (IC207)

■ Picture

- System : Video → PAL/SECAM/NTSC4.43, Sound → Analog
- Progressive
- Output resolution : 1024*768
- OSD : Smart user Interface
- Picture Enhancement : FBE
- Still picture, Noise reduction
- Comb Filter : 3D comb filter
- PIP : Large
- Panorama : Wide

■ Sound

- System : Stereo
- Output : 10W + 10W
- Speaker : built-in

■ Feature

- Component Interface (480i/480p/576i/576p/720p/1080i, Y/Pb/Pr)
- Digital Interface : HDMI
- Picture Size : Auto Wide/16:9/Wide4:3/Zoom/4:3
- Auto Store
- Sleep Timer : 180 minute
- Clock
- Zoom, Previous channel, Blue Screen, Color Tone, Screen Burn Protection

■ Remocon

- TM86B

■ Power Supply

- EU : AC 220-240V, 50Hz
- CIS : AC 100-240V~, 50/60Hz

■ Power Consumption

- Max Power : 360 W

■ Both screen position and size will vary depending on the type of PC monitor and its resolution.

The table below shows all of the display modes that are supported. (N : Negative, P : Positive)

Video Signal	Resolution (Dot X Line)	Vertical frequency (Hz)	Horizontal frequency (kHz)	Vertical polarity	Horizontal polarity
IBM PC / AT Compatible	640 X 350	70.086	31.469	P	N
	720 X 400	70.087	31.469	N	P
	640 X 480	59.940	31.469	N	N
		70.000	35.000	N/P	N/P
		72.809	37.861	N	N
		75.000	37.500	N	N
	800 X 600	56.250	35.156	N/P	N/P
		60.317	37.879	P	P
		70.000	43.750	N/P	N/P
		72.188	48.077	P	P
		75.000	46.875	P	P
	848 X 480	60.000	31.020	P	P
		74.769	37.684	P	N
	1024 X 768	60.004	48.363	N	N
		70.069	56.476	N	N
		72.000	57.672	N/P	N/P
		75.029	60.023	P	P



- ▶ The interlace mode is not supported.
- ▶ The television might operate abnormally if a non-standard video format is selected.
- ▶ 480i/p, 576i/p, 720p, or 1080i is not available in pc mode.
- ▶ The PC text quality is optimum in XGA mode (1024 x 768@60Hz).

■ DTV Specification













Category	Functions	UK	GERMANY
SYSTEM	Broadcasting system Video format Audio format	DVB-T MPEG-2(MP@ML) MPEG-1 audio layer I , II	DVB-T MPEG-2(MP@ML) MPEG-1 audio layer I , II
Channel Parameters	Operational Bands channel range Channel Band width	UHF 21 ~ 68 8 MHz	VHF/UHF 5 ~ 12, 21 ~ 69 VHF-7, UHF-8
EPG	Now/Next Scheduled EPG	○ ○	○ ○
SI	LCN Dynamic SI Replacement Service	○ X X	X X X
CA	CI Embedded CAS Parental Lock	○ (TopUp TV) X ○	○ X ○
System software upgrade	BBC OTA DVB SSU	○ X	X Enhanced profile
Data Service	MHEG MHP	○ (Ver. 1.06) X	X X
Time zone	Time zone setting	X	X
Add-on services	DVB subtitle Teletext AC3 VPS AFD	○ X X X ○	X ○ X ○ X
Etc	Channel list Auto store Manual store Language selection	○ ○ ○ ○	○ ○ ○ ○
Connectors	SPDIF OUT PCMCIA (Type II) RS-232 (Phone Jack) Modem Smart Card	DTV ○ ○ X X	DTV ○ ○ X X

Category	Functions	Sweden	Italy	France
SYSTEM	Broadcasting system Video format Audio format	DVB-T MPEG-2(MP@ML) MPEG-1 audio layer I , II	DVB-T MPEG-2(MP@ML) MPEG-1 audio layer I , II	DVB-T MPEG-2(MP@ML) MPEG-1 audio layer I , II
Channel Parameters	Operational Bands channel range Channel Band width	UHF 21 ~ 69 8 MHz	VHF/UHF 3 ~ 13 (A ~ H2), 21 ~ 69 VHF-7, UHF-8	VHF/UHF 5 ~ 10, 21 ~ 69 VHF-8, UHF-8
EPG	Now/Next Scheduled EPG	○ ○	○ ○	○ ○
SI	LCN Dynamic SI Replacement Service	○ X X	X X X	○ X X
CA	CI Embedded CAS Parental Lock	○ X ○	○ X ○	○ X ○
System software upgrade	BBC OTA DVB SSU	X Simple profile	X Simple profile	X Simple profile
Data Service	MHEG MHP	X X	X ○ (Ver. 1.0.2)	X X
Time zone	Time zone setting	X	X	X
Add-on services	DVB subtitle Teletext AC3 VPS AFD	○ ○ X X X	○ ○ X X X	○ ○ X X X
Etc	Channel list Auto store Manual store Language selection	○ ○ ○ ○	○ ○ ○ ○	○ ○ ○ ○
Connectors	SPDIF OUT PCMCIA (Type II) RS-232 (Phone Jack) Modem Smart Card	DTV ○ ○ X X	DTV ○ ○ ○ ○	DTV ○ ○ X X

2-3 Specifications Analysis

Model		Puccini (V4)	PS-42C7HD (Mustang 42HD)
Design			
Basic	Display Type	PDP TV	PDP TV
	Built-In Tuner	O	O
	Resolution	1024 x 768	1024 x 768
	PDP Module	V4	V5.1
	Screen Size	42 inches	42 inches
	Aspect Ratio	16 : 9	16 : 9
	Power Consumption	380 W	360 W
	Dimensions	1050(W) x 86(D) x 755(H) mm	1055(W) x 340(D) x 758.5(H) mm
	Weight	59.2 Kg	39.5 Kg
Picture	Brightness	1,300 Cd/m2	1,100 Cd/m2
	Contrast Ratio	10,000 : 1	5000:1
	Image Enhancer	DNle-L	FBE
Audio	Equalizer	O	O
	Auto Volume	O	O
	Surround Sound	SRS TruSurround	SRS TruSurround
	Speaker Output	15 W + 15 W	10 W + 10 W
	Speaker	Included	Included
Features	PIP	O	O
	Double Screen	O	X
	TTX	O	O
	Still Image	O	O
	My Color Control	O	X
	Color Weakness	O	X
	Energy Saving	O	O
	Screen Burn Protection	O	O
Connections	Antenna	1 Input	1 Input
	CVBS	1 AV	1 AV
	S-Video	1 Input	1 Input
	Component(Y/PB/PR)	1 Input	1 Input
	PC(D-SUB)	1 Input	1 Input
	DVI	X	X
	HDMI	1 Input	1 Input
	Sub Woofer	X	X
	Optical	X	X
	Coaxial	X	X

2-4 Accessories

Accessories		Item	Item code	Remark
Supplied Accessories		Remote Control Batteries	BN59-00517A 4301-000103	Samsung Service center
		Power Cord	3903-000145	
		Owner's Instructions	BN68-01131A	
		Warranty Card Registration Card Safety Guide Manual	BN68-00514C AA68-03575E AA68-03242E	
Accessories that can be purchased additionally		S-VIDEO Cable	-	Internal shopping mall
		HDMI Cable	-	
		HDMI/DVI cable	-	
		Component Cables (RCA)	-	
		PC Cable	-	
		PC Audio Cable	-	
		Scart Cable	-	
		Antenna Cable	-	

MEMO

3. Alignment & Adjustment

3-1 Service Instruction

■ Before Performing After Sales Services

1. Check if the measurement and test equipment is working properly.
2. Secure sufficient work space for disassembling the product.
3. Prepare a soft pad for disassembling the product.

3-2 How to Access Service Mode

1. General Remote

To Enter : Power Off → INFO → MENU → MUTE → Power On
(Interval between key strokes : less than 3 sec)

To Exit : Power Off → On

2. Settings when entering Factory mode

- Sharp Screen (Dynamic), Color Tone (Cool1), Factory (Dynamic CE Off)

3. Adjustment Procedures

- Channel ▲▼ Key : Select an item.
- Volume ◀▶ Key : Adjust the value up or down.
- MENU Key : Save the changes to the EEPROM and return to the higher-level mode.
- Using the Numeric (0~9) keys, you can select a channel.
- Using the SOURCE key, you can switch AV modes.

4. Initial SERVICE MODE DISPLAY State


```

1. Calibration
2. Option Table XXXX XXXX
3. White Balance
4. SVP-FX
5. Option Block
6. STV8257/STA323W
7. YC Delay
8. Adjust
9. -----
10. W/B MOVIE
11. Checksum
12. Reset
13. -----
    T-MST42PEUHQ-XXXX (Main Micom Ver)
    T-MST42PEUH-XXXX (Sub Micom Ver)
    Month / Day / Year / Hour / Min. / Sec.
    
```

- ※ The version of the firmware displayed at the bottom of the screen may differ and the firmware is subject to change for the improvement of product functions.
- ※ If you have adjusted the settings in Service Mode, you have to reset the product.

3-3 Factory Data

★ The underlined are items applied during the service adjustment. None of the others should be adjusted.



1. Calibration
 2. Option Table XXXX XXXX
 3. White Balance
 4. SVP-FX
 5. Option Block
 6. STV8257/STA323W
 7. YC Delay
 8. Adjust
 9. -----
 10. W/B MOVIE
 11. Checksum
 12. Reset
 13. -----
 T-MST42PEUHQ-XXXX (Main Micom Ver)
 T-MST42PEUH-XXXX (Sub Micom Ver)
 Month / Day / Year / Hour / Min. / Sec.



4. SVP-PX	: SVP-PX Correct Register				
ComB Filter	: Y-Filter - 80H				
Sharpness	:	RF/AV	COMP	PC	HDMI
H2Gain		08H	10H	10H	08H
H4Gain		04H	04H	04H	00H
V2Gain		08H	10H	10H	08H
V4Gain		04H	04H	04H	04H
Sr2Gain		00H	00H	00H	00H
Sr4Gain		00H	00H	00H	00H
SI2Gain		00H	00H	00H	00H
SI4Gain		00H	00H	00H	00H
Peakth1		00H	00H	00H	00H
Peakth2		80H	80H	80H	80H
Peakth3		00H	00H	00H	00H
NR	:	YNROFF	80H		
		CNROFF	80H		
		YNRON	80H		
		CNRON	80H		
RGB Calibration	:	RF/AV	COMP	PC	HDMI
R-Offset		4EH	4CH	49H	48H
G-Offset		4EH	4CH	49H	48H
B-Offset		4EH	4CH	49H	48H
R-Gain		7CH	7BH	78H	9DH
G-Gain		7CH	7BH	80H	9DH
B-Gain		7CH	7BH	7AH	9DH
ADC Calibration	:	RF/AV	COMP	PC	HDMI
TCD3 Contrast		82H	78H	78H	78H
TCD3 Brightness		21H	20H	20H	20H
TCD3 CR		80H	80H	80H	80H
TCD3 CB		80H	80H	80H	80H
TCD3 Delay		00H	00H	00H	00H
Analog Y Offset		40H	40H	42H	40H
Analog PB Offset		80H	80H	38H	80H
Analog PR Offset		80H	80H	39H	80H
Analog Y Gain		D6H	DAH	D0H	D6H
Analog PB Gain		FEH	9AH	80H	FEH
Analog PR Gain		FEH	9AH	80H	FEH
Black Level		00H	00H	00H	00H
SVP Brightness		00H	00H	00H	00H
Calibration Target	:	low	high	delta	
AV ADC		10H	F8H	04H	
COMP ADC		10H	F8H	04H	
PC ADC		10H	F8H	04H	
ALL RGB		04H	F8H	10H	


1. Calibration
 2. Option Table XXXX XXXX
 3. White Balance
 4. SVP-FX
 5. Option Block
 6. STV8257/STA323W
 7. YC Delay
 8. Adjust
 9. -----
 10. W/B MOVIE
 11. Checksum
 12. Reset
 13. -----
 T-MST42PEUHQ-XXXX (Main Micom Ver)
 T-MST42PEUH-XXXX (Sub Micom Ver)
 Month / Day / Year / Hour / Min. / Sec.

5. Option Block

FRC-Micronas		
FRC-Samsung		
LBE/FBE	: Test Pattern	00H
	Black Stretch Tilt	50H
	Black Stretch Gain	55H
	Black Stretch Ratio	33H
	Skin En	01H
	Skin Gain	80H
	Skin T X	6EH
	Skin T Y	60H
	White En	00H
	MCM Gain	80H
	White T X	4FH
	White T Y	54H
	CHY Gain1	3EH
	CHY Gain2	42H
	CHC Gain1	40H
	CHC Gain2	40H
	CHM Gain1	3DH
	CHM Gain2	45H
	ColorGain TY	00H
	ColorGain TC	00H
	ColorGain TM	00H
	Color Gain	80H
	Input RGB Gain	80H
	Input RGB Offset	00H

6. STV8257/STA323W : Sound IC Correct Register

Ch1 Volume	: 55H
Ch2 Volume	: 55H
AGC Gain	: 05H
AM Prescale	: 00H
ZWT TH	: 0AH
AV Delay	: 55H
Comp Delay	: 32H
HDMI Delay	: 32H
PC Delay	: 32H
L1 Att/Rel Th	: EDH



1. Calibration
2. Option Table XXXX XXXX
3. White Balance
4. SVP-FX
5. Option Block
6. STV8257/STA323W
7. YC Delay
8. Adjust
9. -----
10. W/B MOVIE
11. Checksum
12. Reset
13. -----

T-MST42PEUHQ-XXXX (Main Micom Ver)
 T-MST42PEUH-XXXX (Sub Micom Ver)
 Month / Day / Year / Hour / Min. / Sec.

10. W/B MOVIE

	RF/AV	COMP	PC	HDMI
WB Movie	OFF	OFF	OFF	OFF
Color Mode	Movie	Movie	Movie	Movie
Color Tone	Warm2	Warm2	Warm2	Warm2
W1 R Gain	131	131	130	132
W1 B Gain	118	117	119	118
W1 R Offset	131	129	138	128
W1 B Offset	127	131	115	129
W2 R Gain	133	133	134	134
W2 B Gain	104	109	115	110
W2 R Offset	127	128	141	128
W2 B Offset	132	120	113	119
Movie Contrast	70	70	70	70
Movie Brightness	50	50	50	50
Movie Color	45	45	45	45
Movie Sharpness	25	25	25	25

11. Checksum

12. Reset

13. -----

3-4 Service Adjustment


3-4-1 White Balance - Calibration

If picture color is wrong, do calibration first.

Execute calibration in Factory Mode

1. Source : VIDEO
2. Setting Mode : PAL Video (MODE : #2)
3. Pattern : Pattern #24 (Chess Pattern)
4. Use Equipment : K-7256 or Equipment of equality level
5. Work order
 - 1) Enter by Factory Mode select "1.CALIBRATION".
 - 2) Select "AV CALIBRATION" again in CALIBRAION MENU.
 - 3) After Completing Calibration, come out "Av success". OSD on the screen (bottom-side) for about 3 seconds.

Source AV : PAL composite, Component : 1280*720/60Hz
PC : 1024*768/60Hz




(Chess Pattern)

3-4-2 White Balance - Adjustment

If picture color is wrong, check White Balance condition.

Equipment : CA210, Patten : Toshiba
Adjust W/B in Factory Mode

Sub brightness and R/G/B Offset controls low light region
Sub contrast and R/G/B Gain controls high light region
Source AV : PAL composite, Component : 1280*720/60Hz,
HDMI[DVI] : 1280*720/60Hz



(SAMSUNG WHITE BALANCE Adjustment PATTERN with FPD)

[Test Pattern : MSPG-945 Series Pattern #16]

* Color temperature
1500K +/-500, -6 ~-20 MPCD

* Color coordinate
H/L : 278/285 +/- 2
L/L : 278/285 +/- 3, 2.1 Ft +/-0.05 Ft

3-4-3 Conditions for Measurement

- On the basis of toshiba ABL pattern : High Light level (57 IRE)
 - INPUT SIGNAL GENERATOR : MSPG-925LTH
 - * Mode No 2 : 744X484@60 Hz
 - No 6 : 1280X720@60 Hz
 - No 21 : 1024X768@60 Hz
 - * Pattern No 36 : 16 Color Pattern
 - No 16 : Toshiba ABL Pattern
- Optical measuring device : CA210 (FL)
 - Please use the MSPG-925 LTH generator for model PS-42E7H / PS-42E7HD / PS-42C7HD.

3-4-4 Method of Adjustment

1. Adjust the white balance of AV, Component and DVI Modes.

(AV → Component)


a) Set the input to the mode in which the adjustment will be made (RF → DTV → PC → DVI).

- * Input signal - VIDEO Mode : Model #2 (744*484 Mode), Pattern #16
- DTV, DVI Mode : Model #6 (1280*720 Mode), Pattern #16
- HDMI Mode : Model #6 (1280*720 Mode), Pattern #16

b) Enter factory color control, confirm the data.

c) Adjust the low light. (Refer to table 1, 2 in adjustment position by mode)

- Adjust sub - Brightness to set the 'Y' value.
- Adjust red offset ('x') and blue offset ('y') to the color coordinates.




(SAMSUNG WHITE BALANCE Adjustment PATTERN with FPD)

* Do not adjust green offset data.

d) Adjust the high light. (Refer to table 1, 2 in adjustment position by mode)

- Adjust red gain ('x') and blue gain ('y') to the color coordinates.



(SAMSUNG WHITE BALANCE Adjustment PATTERN with FPD)

* Do not adjust the green gain and sub-contrast (Y) data.

3-5 Software Upgrade

3-5-1 How to Update Flash ROM


1. Install the Flash Downloader

Connect Set (Service Jack) and Jig Cable to execute Program Update.



2. Flash Downloader program update

- Before Turning on the set, Click "connect" which is under of OSD Screen.
- Turn on the Set.



3-5-2 How to Update DTV Software

1. Software Version Check Method

Press the MENU key and select System.

Where you can find the Product Information menu in it.

When you press the Product Information you can find the Software Version.

Connect Set (Service Jack) and Jig Cable to execute Program Update.

2. Serial Download Method

① Turn off PDP-TV.

② Connect the RS-232 cable to the PDP-TV

③ Execute the sv2_fr.exe file.

④ Assign the path of samsung.tvz file (application image)

⑤ Execute the progress follow the screen until step 2.

⑥ Turn On the PDP-TV.

⑦ If the PDP-TV turn on during the sv2_fr.exe execution, it will automatically find the COM port and execute the upgrade.

3. Hyper Terminal Setting

Set the hyper terminal to observe the progress of the TV via the RS-232 cable. Set up hyper terminal.

① When setting up a hyper terminal, set it in sub-program.

② Enter a new name.

③ Select a modem port. (com 1 and direct connection.)

④ Set the bit/second to 115200.

⑤ Set the data bit to 8.

⑥ No parity bit.

⑦ Set stop bit to 1.

⑧ No flow control.

⑨ Save in memory.

⑩ At this point, the new hyper terminal is ready.

4. Resetting the System Parameters

① Press the MENU button and select the Reset menu of System.

② Press the secret number.

③ Press the RED, GREEN, YELLOW, BLUE button in order, after the Reset execute.

④ In a few minutes, DTV will booting again.

3-6 Replacements & Calibration

※ The ASSY code can be changed, see "5. Electrical Part List."

* Check items listed after changing each


Replaced Items	Code No.	Check Items
ASSY PCB MISC-MAIN	BN94-01144A	1) Auto Program 2) White Balance Adjust
ASSY PCB P-SMPS(MAIN)	BN96-03743A	Vs, Va voltage check and adjust
ASSY PCB P-SMPS(DC DC)	BN96-01856A	Vscan, Vset, Ve voltage check and adjust
ASSY PDP P-LOGIC BOARD	BN96-04177A	Not adjustment
ASSY PDP P-X MAIN BOARD	BN96-03350A	
ASSY PDP P-Y MAIN BOARD	BN96-03351A	
ASSY PDP P-Y MAIN SCAN BOARD	BN96-03352A	
ASSY PDP P-ADDRESS E BUFF BOARD	BN96-03353A	
ASSY PDP P-ADDRESS F BUFF BOARD	BN96-03354A	

※ When replacing the SMPS (DC DC) or PDP panel, you have to check the voltage printed on the panel sticker and adjust it.


3-6-1 Voltage Adjustment

1. After replacing the SMPS or PDP panel, you must adjust the voltage referring to the voltage label printed on the panel.
(If you do not adjust the voltage, an abnormal discharge symptom may appear.)


	Value	Board Adjustment
Vs	200	SMPS-MAIN
Va	65	
Vset	195	SMPS-DC/DC
Ve	120	
Vscan	-190	



2. A point of adjusting SMPS-MAIN voltage.



3. A point of adjusting SMPS-DC/DC.




* Use base chassis of PDP panel as GND point.

MEMO

4. Exploded View & Part List

4-1 PS42C7HDX/XET

You can search for the updated part code through ITSELF web site.
URL:<http://itself.sec.samsung.co.kr>



Loc. No.	Code No.	Description	Specification	Q'ty	SA/SNA	Remark
CIS7	AA61-60003B	SPRING ETC-CS	-,SUS304,-,-,OD11.2,N7,OD1	1	S.N.A	
M0006	BN63-02383D	COVER-REAR	42Q7,PCM,T0.5,MMS,PAL	1	S.N.A	
M0013	BN96-03154B	ASSY STAND P-BASE	C7,HGI T3.0,BKP-1526,R	1	S.A	
M0013	BN96-03160G	ASSY COVER P-REAR	42C7,PCM,T0.5,MMS,PAL	1	S.A	
M0020	BN96-04184C	ASSY BOARD P-SIDE AV	ALPS,SJ06-01-015C,S	1	S.A	
M0107	BN61-02315J	BRACKET-PCB	P7,SECC,T0.8,Alps,Himalaya	1	S.N.A	
M0111	BN63-02387A	COVER-STAND	42C7,HIPS,HB,BKP-1526	1	S.N.A	
M0112	BN63-02375M	COVER-FRONT	42C7HD,HIPS,HB,XET,GRAY,BKP-	1	S.N.A	
M0115	BN61-02659A	BRACKET-STAND	42C7,HGI,T2.0	1	S.N.A	
M0145	BN96-02784B	ASSY BOARD P-FUNCTION	CADILLAC,SJ06-01-0	1	S.A	
M0150	BN96-04343A	ASSY BRACKET P-FILTER BOTTOM	42C7,AL	1	S.N.A	
T0003	BN96-03762M	ASSY COVER P-FRONT	42C7HD(HQ),XET,HIPS H	1	S.A	
T0023	BN96-03173A	ASSY COVER P-KNOB POWER	42P7,ABS	1	S.A	
T0023	BN64-00459A	KNOB POWER	42P7,PC,Violet	1	S.N.A	
T0044	BN96-04174A	ASSY PDP MODULE P	42HD,W1,1024*768,compl	1	S.A	
T0059	BN64-00461A	INDICATOR LED	42P7,PMMA	1	S.N.A	
T0061	BN64-00462A	WINDOW-REMOCON	42P7,ACRYL,5%	1	S.N.A	
T0074	BN59-00517A	REMOCON	SORRENTO,TM87B,45,SORRENTO,EUROP	1	S.A	
T0079	BN94-01144A	ASSY PCB MISC-MAIN	PS42Q7HDX/XET,D74B,BN	1	S.A	
T0175	BN96-02785A	ASSY SPEAKER P	8ohm,Twister,42inch,10W	1	S.A	
T0268	3903-000145	CBF-POWER CORD	DT,EU,FP3/YES,U(IEC C13-R	1	S.A	
T0422	BN94-01023B	ASSY PCB MISC-DTV MODULE	PS42Q7HD/PS42Q7	1	S.N.A	
T0448	BN96-03144Q	ASSY BRACKET P-TERMINAL	P7,EU(IDTV),SECC	1	S.N.A	
T0456	BN67-00177A	GLASS-FILTER EMI	42" C7 V5.1,Sputter,T=4	1	S.A	
T0603	BN64-00460A	KNOB-DECORATION POWER	42P7,ABS,HB,AL	1	S.N.A	

5. Electrical Part List

5-1 PS42C7HDX/XET Service Item

You can search for the updated part code through ITSELF web site.

URL:<http://itself.sec.samsung.co.kr>

Loc. No.	Code No.	Description	Specification	Q'ty	SA/SNA	Remark
M0013	BN96-03154B	ASSY STAND P-BASE	C7,HGI T3.0,BKP-1526,R	1	S.A	
M0013	BN96-03160G	ASSY COVER P-REAR	42C7,PCM,T0.5,MMS,PAL	1	S.A	
M2893	BN39-00632B	LEAD CONNECTOR	PS-42E7HX/XEC,UL1617#22,U	1	S.A	
M2893	BN39-00667D	LEAD CONNECTOR-LVDS	AUDI,UL20276#30,31PI	1	S.A	
M2893	BN39-00675A	LEAD CONNECTOR	PUCCINI,UL1007#26,10PIN,1	1	S.A	
M2893	BN39-00676A	LEAD CONNECTOR	PUCCINI,UL1007#26,12PIN,1	1	S.A	
M2893	BN39-00759A	LEAD CONNECTOR	AUDI,UL1007#26,UL/CSA,2PI	1	S.A	
MD101	BN96-02795A	ASSY PCB P-MODEM	SIENA,ITALY,MODEM	1	S.A	
T0003	BN96-03762M	ASSY COVER P-FRONT	42C7HD(HQ),XET,HIPS H	1	S.A	
T0044	BN96-04174A	ASSY PDP MODULE P	42HD,W1,1024*768,compl	1	S.A	
T0074	BN59-00517A	REMOCON	SORRENTO,TM87B,45,SORRENTO,EU	1	S.A	
T0079	BN94-01144A	ASSY PCB MISC-MAIN	PS42Q7HDX/XET,D74B,BN	1	S.A	
T0159	BN96-01856A	ASSY PCB P-SMPS	SPD-50P5HD(DC_DC),200Vin	1	S.A	
T0159	BN96-03743A	ASSY PCB P-SMPS	PS42E7H,Free-Volt,245*37	1	S.A	
T0175	BN96-02785A	ASSY SPEAKER P	8ohm,Twister,42inch,10W	1	S.A	
T0245	BN39-00164A	LEAD CONNECTOR-ASSY	GH15LS/MS,UL/CSA,1P,	1	S.A	
T1910	BN96-03350A	ASSY PDP MODULE P-X MAIN BOARD	42HD,PL42	1	S.A	
T1911	BN96-03351A	ASSY PDP MODULE P-Y MAIN BOARD	42HD,PL42	1	S.A	
T1914	BN96-03353A	ASSY PDP MODULE P-ADDRESS E BU	42HD,PL42	1	S.A	
T1915	BN96-03354A	ASSY PDP MODULE P-ADDRESS F BU	42HD,PL42	1	S.A	
T1917	BN96-04177A	ASSY PDP MODULE P-LOGIC MAIN	42HD,W1,102	1	S.A	
T9698	BN96-03352A	ASSY PDP MODULE P-Y MAIN SCAN	42HD,PL42A	1	S.A	

MEMO


6. Troubleshooting

6-1 First Checklist for Troubleshooting


1. Check the various cable connections first.
 - Check to see if there is a burnt or damaged cable.
 - Check to see if there is a disconnected cable connection or a connection is too loose.
 - Check to see if the cables are connected according to the connection diagram.
2. Check the power input to the Main Board.
3. Check the voltage in and out between the SMPS ↔ Main Board, between the SMPS ↔ X, Y Main Board, and between the Logic Boards.

6-2 Checkpoints by Error Mode


6-2-1 No Power

Symptom	<ul style="list-style-type: none"> - The LEDs on the front panel do not work when connecting the power cord. - The SMPS relay does not work when connecting the power cord. - The power of the unit seems to be out of order.
Major Checklist	<p>The SMPS relay or the LEDs on the front panel does not work when connecting the power cord if the cables are improperly connected or the Main Board or SMPS is out of order. In this case, check the following:</p> <ul style="list-style-type: none"> - Check the internal cable connection status inside the unit. - Check the fuses of each part. - Check the output voltage of SMPS. - Replace the Main Board.
Troubleshooting Procedures	 <pre> graph TD Q1_1[1 Are the AC IN socket connector and the Main SMPS CN800 connected?] -- No --> A1_1([The AC IN socket connector and the Main SMPS CN800 connected]) Q1_1 -- Yes --> Q1_2[1 Is the Fuse (F801S) of the Main SMPS Power Input Part blown?] Q1_2 -- No --> A1_2([Replace Fuse (F801S)]) Q1_2 -- Yes --> Q2_1[2 Main SMPS CN804-1 Pin 3 : STB 5V Pin 8 PS-ON : Check to see if it is 0V] Q2_1 -- No --> A2_1([Replace the Main SMPS]) Q2_1 -- Yes --> A2_2[Replace the Main Board] </pre>


6-2-2 When the unit is repeatedly turned on and off

Symptom	- The SMPS relay is repeatedly turned on and off.
Major Checklist	<p>In general, the SMPS relay repeatedly turns on and off by the protection function due to a defect on a board connected to the SMPS.</p> <ul style="list-style-type: none"> - Disconnect all cables from the SMPS, operate the SMPS alone and check if the SMPS works properly and if each voltage output is correct. - If the symptom continues even when SMPS is operated alone, replace the SMPS. - If the symptom is not observed when operating the SMPS alone, find any defective ASSYs by connecting the cables one by one.
Troubleshooting Procedures	 <pre> graph TD Q1["① Does the symptom continue after connecting the power and removing the CN809 cable from the Main SMPS?"] Q2["② Does the symptom continue after connecting the power and removing the CN804-2 cable from the Main SMPS?"] Q3a["③ Does the symptom continue when connecting the power after connecting the CN809 cable and removing the CN1, CN2, CN4 and CN6 cables from the DC-DC SMPS?"] Q3b["③ Does the symptom continue when connecting the power after removing the CN4 cable from the DC-DC SMPS?"] Q3c["③ Does the symptom continue when connecting the power after removing CN2 from the DC-DC SMPS?"] Q4["② Does the symptom continue when connecting the power after removing CN810 from the Main SMPS?"] R1["Replace the DC-DC SMPS"] R2["Replace the Main SMPS"] R3a["Replace the X Main Board"] R3b["Replace the Y Main Board"] R4["Replace the Logic Board"] Q1 -- Yes --> R2 Q1 -- No --> Q3a Q2 -- Yes --> R2 Q2 -- No --> Q3a Q3a --> R1 Q3a --> Q3b Q3b --> R3a Q3b --> Q3c Q3c --> R3b Q3c --> Q4 Q4 --> R4 </pre>
Caution	When separating and connecting the cables such as CN809 of the Main SMPS, CN1, CN2, CN3, CN4 and CN5 of DC-DC SMPS, CN4004 of the X Main Board, and CN5010 of the Y Main Board, a spark may be generated by the electric charge of the high capacity capacitor. Therefore, wait some time after separating the power cord from the unit.


6-2-3 No Picture (When audio is normal)

Symptom	- Audio is normal but no picture is displayed on the screen.
Major Checklist	<ul style="list-style-type: none"> - This may happen when the Main Board is normal but the X, Y Main Board, Logic Board, or Y Buffer Boards are out of order. - The output voltage of the Main SMPS or the DC-DC SMPS is out of order. - This may happen when the LVDS cable connecting the Main Board and the Logic Board is disconnected.
Troubleshooting Procedures	 <pre> graph TD Q1["① Are the Vs and Va voltages normal after removing the CN809 cable from the Main SMPS?"] A1_Yes["Yes"] A1_No["No"] R1["Replace the Main SMPS"] Q2["② Is the output voltage of the DC-DC SMPS normal when reconnecting the CN809 cable and removing the CN1, CN2, CN4 and CN6 cables from the DC-DC SMPS?"] A2_Yes["Yes"] A2_No["No"] R2["Replace the DC-DC SMPS"] R3["Replace the Y Main Board"] R4["Replace the X Main Board"] R5["Replace the Logic Board"] R6["Replace the Y Scan Board"] Q1 --> Yes A1_Yes Q1 --> No A1_No A1_No --> R1 A1_Yes --> Q2 Q2 --> Yes A2_Yes Q2 --> No A2_No A2_No --> R2 A2_Yes --> R3 R3 --> R4 R4 --> R5 R5 --> R6 </pre>
Caution	When separating and connecting the cables such as CN809 of the Main SMPS, CN1, CN2, CN3, CN4 and CN5 of DC-DC SMPS, CN4004 of the X Main Board, and CN5010 of the Y Main Board, a spark may be generated by the electric charge of the high capacity capacitor. Therefore, wait some time after separating the power cord from the unit.


6-2-4 No Sound

Symptom	- Video is normal but there is no sound.
Major Checklist	- When the speaker connectors are disconnected or damaged. - When the sound processing part of the Main Board is out of order. - Speaker defect.
Troubleshooting Procedures	<div></div> <div><div><div>①</div><div>Is the cable connection between the Main Board and the speaker properly connected?</div><div>No</div><div>Connect the cable properly or replace the cable, if necessary.</div><div>Yes</div></div><div><div>②</div><div>Is the output voltage of SMPS normal? (CN803 #5)</div><div>No</div><div>Replace the Main SMPS</div><div>Yes</div></div><div><div>Is the speaker output terminal of the Main Board normal?</div><div>No</div><div>Replace the Main Board</div><div>Yes</div></div><div><div>③</div><div>Replace the Speaker</div></div></div>

6-2-5 No Video

Symptom	- A normal/cable network analog broadcast screen is blank or abnormal but OSD is OK.
Major Checklist	<ul style="list-style-type: none"> - Check the antenna connection settings (Antenna 1 - Normal/Cable/DTV, Antenna 2 - Only for DTV) - Check the tuner output signal (CVBS). - Check the power input of the Main board.
Troubleshooting Procedures	 <pre> graph TD Q1[Is the antenna connection setting properly configured?] -- No --> A1[Configure properly] Q1 -- Yes --> Q2[1 Check CN101 pin2 for +33V] Q2 -- No --> A2[Replace the Main SMPS] Q2 -- Yes --> A3[Replace the Main Board] </pre> <p>The troubleshooting procedure for 'No Video' is as follows:</p> <ol style="list-style-type: none"> Is the antenna connection setting properly configured? <ul style="list-style-type: none"> If No: Configure properly. If Yes: Proceed to step 1. 1 Check CN101 pin2 for +33V <ul style="list-style-type: none"> If No: Replace the Main SMPS. If Yes: Replace the Main Board.

6-2-6 Main SMPS Troubleshooting



6-2-7 Drive Board Troubleshooting

1) Troubleshooting Summary




Condition Name	Description	Related Board
No Voltage Output	Operating Voltages don't exist	PSU
No Display	Operating Voltages exist, but an Image doesn't exist on screen	Y-MAIN, X-MAIN, Logic Main, Cable
Abnormal Display	Abnormal Image (not open or short) is no screen	Y-MAIN, X-MAIN, Logic Main
Sustain Open	Some horizontal lines don't exist on screen	Scan Buffer, FPC of X/Y
Sustain Short	Some horizontal lines appear to be linked on screen	Scan Buffer, FPC of X/Y
Address Open	Some vertical lines don't exist on screen	Logic Main, Logic Buffer, TCP
Address Short	Some vertical lines appear to be linked on screen	Logic Main, Logic Buffer, TCP

2) Troubleshooting Procedure in Abnormal Conditions

① No Display (Operating Voltage exist, but an doesn't exist on Screen)

- No Display is related with Y-MAIN, X-MAIN, Logic Main and so on.


This page shows you how to check the boards, and the following pages show you how to find the defective board.




② Abnormal Display(Abnormal Image is on Screen.(except abnormality in Sustain or Address)

- Abnormal Display is related with Y-MAIN, X-MAIN, Logic Main and so on.


This page shows you how to check the boards, and the following pages show you how to find the defective board.



③ Sustain Open (some horizontal lines don't exist on screen)




④ Sustain Short (some horizontal lines appear to be linked on Video)



⑤ Address Open, Short(some vertical lines don't exist on screen)

- Address Open and Short is related with Logic Main, Logic Buffer, FFC, TCP film and so on.


This page shows you how to check the boards, and the following pages show you how to find the defective board.



6-3 Troubleshooting Procedures by ASS'Y

※ The ASS'Y code can be changed, see "5. Electrical Part List."


No	Assy	Code No.	Description	Major Symptoms
1	ASSY PCB P-SMPS	BN96-03743A	Main SMPS	No power, Blank screen, the Relay repeats On and Off.
2	ASSY PCB P-SMPS	BN96-01856A	DC-DC SMPS	Blank screen, the Relay repeats On and Off.
3	ASSY PDP P-X MAIN BOARD	BN96-03350A	X Main Board	Blank screen
4	ASSY PDP P-Y MAIN BOARD	BN96-03351A	Y Main Board	Blank screen
5	ASSY PDP P-LOGIC MAIN BOARD	BN96-04177A	Logic Board	Blank screen, Screen noise
6	ASSY PDP P-Y SCAN BOARD	BN96-03352A	Y Scan Board	Row Bar screen is blank
7	ASSY PDP P-ADDRESS E-BUFF BOARD	BN96-03353A	Address E Buffer Board	Corresponding Buffer Board block screen is blank.
8	ASSY PDP P-ADDRESS F-BUFF BOARD	BN96-03354A	Address F Buffer Board	Corresponding Buffer Board block screen is blank.
9	ASSY PCB MISC-MAIN ASSY PCB MISC-DTV MODULE	BN94-01144A BN94-01023B	Main Board DTV Module Board	No Power, Abnormal screen for each input source, PIP screen trouble, Sound trouble
10	ASSY BOARD P-FUNCTION	BN96-02784B	Function Key Board	The side function key does not work properly
11	ASSY BOARD P-POWER&IR	BN96-03320B	Power Button Board	The remote control does not work properly, the LED does not work properly.
12	ASSY BOARD P-SIDE AV	BN96-04184C	Side AV Board	The AV2 and S-VIDEO2 modes do not work properly



MEMO

7. Block Diagram

7-1 Overall Block Diagram




CN804-1(Main SMPS) ↔ CN102(Main Board)		CN803(Main SMPS) ↔ CN101(Main Board)		CN810(Main SMPS) ↔ CN2013(Logic Board)		CN2(DC-DC SMPS) ↔ CN5007(Y B'D)		CN4(DC-DC SMPS) ↔ CN4001(X B'D)	
Pin No.	Signal	Pin No.	Signal	Pin No.	Signal	Pin No.	Signal	Pin No.	Signal
1	5.3V	1	6.5V	1	STBY	1	Vs	1	D5.3V
2	RTN	2	RTN	2	VS_ON	2	Vs	2	Vg
3	N/C	3	12V	3	N/C	3	RTN	3	RTN
4	N/C	4	RTN	4	PS_ON	4	RTN	4	RTN
5	RTN	5	18Vamp	5	RTN	5	Vset	5	Ve
6	RTN	6	18Vamp	6	5.3V	6	RTN	6	RTN
7	12V	7	RTN_amp	7	RTN	7	Vscan	7	RTN
8	PS_ON	8	RTN_amp	8	RTN	8	RTN	8	Vs
9	RTN	9	Vt	9	5.3V	9	Vg	9	Vs
10	STBY	10	RTN	10	5.3V	10	D5.3V		
11	FAN_ON								
12	FAN_D								


CN6(DC-DC SMPS) ↔ CN2509(E-Buffer)	
Pin No.	Signal
1	RTN
2	N.C
3	D5.3V
4	N/C
5	Va

7-2 Partial Block Diagram

7-2-1 Audio/Video Signal Block Diagram




7-2-2 DC-DC SMPS Block Diagram




7-2-3 Module Driver Board Block Diagram


1. Y Drive Board




2. X Drive Board




7-2-4 Logic Board Block Diagram



7-2-5 Main Board Block Diagram



7-2-6 DTV Module Board Block Diagram



8-1 Overall Wiring

The diagram illustrates the internal wiring of a car stereo unit. Key components and their connections are as follows:


- 1 SMPS-MAIN**: Main power supply unit, connected to the AC-INLET (15) and the SMPS-DC (2).
- 2 SMPS-DC**: DC power supply unit, connected to the SMPS-MAIN (1) and the X-DRIVE (3).
- 3 X-DRIVE**: Drive unit for the X-axis, connected to the SMPS-DC (2) and the X-DRIVE (3).
- 4 Y-DRIVE**: Drive unit for the Y-axis, connected to the Y-BUFFER (5) and the Y-DRIVE (4).
- 5 Y-BUFFER**: Buffer unit for the Y-axis, connected to the Y-DRIVE (4) and the Y-BUFFER (5).
- 6 LOGIC BOARD**: Central control unit, connected to the SMPS-MAIN (1), SMPS-DC (2), and various other components.
- 7 E-BUFFER**: Buffer unit for the E-axis, connected to the E-BUFFER (7) and the E-BUFFER (7).
- 8 F-BUFFER**: Buffer unit for the F-axis, connected to the F-BUFFER (8) and the F-BUFFER (8).
- 9 MAIN BOARD**: Main control unit, connected to the LOGIC BOARD (6), DIGITAL BOARD (10), and various other components.
- 10 DIGITAL BOARD**: Digital control unit, connected to the MAIN BOARD (9) and the DIGITAL BOARD (10).
- 11 POWER SW**: Power switch, connected to the MAIN BOARD (9) and the POWER SW (11).
- 12 SPEAKER**: Speaker unit, connected to the MAIN BOARD (9) and the SPEAKER (12).
- 13 SIDE AV**: Side audio input, connected to the MAIN BOARD (9) and the SIDE AV (13).
- 14 FUNCTION**: Function button, connected to the MAIN BOARD (9) and the FUNCTION (14).
- 15 AC-INLET**: AC power inlet, connected to the SMPS-MAIN (1) and the AC-INLET (15).

Connectors and components are labeled with CN (connector) and C (component) followed by a number. The diagram shows a complex network of wires connecting these components, with some components having multiple connections.

No	Assy	Code No.	Description
—	ASSY PDP MODULE P	BN96-04174A	42HD,W1,1024*768,complementary color,sec/ t/sec only,third
①	ASSY PCB P-SMPS	BN96-03743A	PS42E7H,Free-Volt,245*370mm
②	ASSY PCB P-SMPS	BN96-01856A	SPD-50P5HD(DC_DC),200Vin(DC_DC)
③	ASSY PDP MODULE P-X MAIN BOARD	BN96-03550A	42HD,PL42AX005A,V5.1,NTSC/PAL,1024*768,LJ92-01345A
④	ASSY PDP MODULE P-Y MAIN BOARD	BN96-03351A	42HD,PL42AX005A,V5.1,NTSC/PAL,1024*768,LJ92-01346A
⑤	ASSY PDP MODULE P-Y MAIN SCAN BUFFER	BN96-03352A	42HD,PL42AX005A,V5.1,NTSC/PAL,1024*768,LJ92-01344A
⑥	ASSY PDP MODULE P-LOGIC MAIN BOARD	BN96-04177A	42HD,W1,1024*768,SEC/TTEsc only,LJ92-01432A,third line
⑦	ASSY PDP P-ADDRESS E BUFFER	BN96-03353A	42HD,PL42AX005A,V5.1,NTSC/PAL,1024*768,LJ92-01343A
⑧	ASSY PDP P-ADDRESS F BUFFER	BN96-03354A	42HD,PL42AX005A,V5.1,NTSC/PAL,1024*768,LJ92-01342A
⑨	ASSY PCB MISC-MAIN	BN94-01144A	PS42Q7HDX/XET,D74B,BN41-00766A,Sputter
⑩	ASSY PCB MISC-DTV MODULE	BN94-01023B	PS42C7HD/42Q7H DU,D74B,XET,BN1-00660E
⑪	ASSY BOARD P-POWER&IR	BN96-03320B	ALPS,SJ06-01-017A,SUNGJI,POWER&IR,HARNESS 8P,1.6T 74
⑫	ASSY SPEAKER P	BN96-02785A	8ohm,Twister,42inch,10W
⑬	ASSY BOARD P-SIDE AV	BN96-04184C	ALPS,SJ06-01-015C,SIDE-AV,400mm
⑭	ASSY BOARD P-FUNCTION	BN96-02784B	CADILLAC,SJ06-01-006,FUNCTION,600MM, CORE
⑮	FILTER-EMI AC LINE	2901-001378	250V,6A,-,0.15uF/1000pF,50x22.5x37.2mm,BK,-

8-2 Partial Wiring





8-2-1 PDP Module ↔ SMPS Wiring



① CN809(Main SMPS) ↔ CN3(DC-DC SMPS)		② CN2(DC-DC SMPS) ↔ CN5007(Y B'D)		③ CN4(DC-DC SMPS) ↔ CN4001(X B'D)		④ CN6(DC-DC SMPS) ↔ CN2509(E-Buffer)		⑤ CN810(Main SMPS) ↔ CN2013(Logic B'D)	
Pin No.	Signal	Pin No.	Signal	Pin No.	Signal	Pin No.	Signal	Pin No.	Signal
1	D5.3V	1	Vs	1	D5.3V	1	RTN	1	STD_5V
2	Vg	2	Vs	2	Vg	2	N.C	2	VS_ON
3	RTN	3	RTN	3	RTN	3	D5.3V	3	N/C
4	RTN	4	RTN	4	RTN	4	N/C	4	PS_ON
5	RTN	5	Vset	5	Ve	5	Va	5	RTN
6	RTN	6	RTN	6	RTN			6	D5.3V
7	RTN	7	Vscan	7	RTN			7	RTN
8	Va	8	RTN	8	Vs			8	RTN
9	Va	9	Vg	9	Vs			9	D5.3V
10	N/C	10	D5.3V					10	D5.3V
11	Vs								
12	Vs								

8-2-2 Connect Cables


※ The code number of cable(Lead-connector) can be changed, see "5 Chapter. Electrical Part List."

Use	SMPS 12P	LVDS 31P	POWER 10P
Code	BN39-00632B	BN39-00667D	BN39-00675A
Photo			
Use	POWER 12P		
Code	BN39-00676A		
Photo			


MEMO

9. PCB Diagram

9-1 MAIN & DTV MODULE Board



No	Name	Function	Description
①	SVP-PX	Scaler IC Controller	SVPTMPX contains dual-purposed triple 10-bit high-precision and high speed video ADCs for both PC and video inputs, the high speed HDMI could support all HDMI inputs up to 135MHz with HDCP format, the highperformance multi-format 3D digital comb video decoder that supports NTSC, PAL, and SECAM*, a HDTV sync separator, motion adaptive de-interlacing engine, and the video format conversion engine, supporting multi-window display in many different output modes.
②	M30840SGP	IC MICOM	With a 16-Mbyte address space, this microcomputer combines advanced instruction manipulation capabilities to process complex instructions by less bytes and execute instructions at higher speed.
③	FRC	IC DNle	Image enhancement IC
④	DOCS403ZH261B (S)	TUNER	Tuner CH Tuning
⑤	STA323W	IC AUDIO-AMP	Audio power amplifiers



① CN2013(Logic B'd) ↔ CN902(Main Board)					
Pin No.	Signal	Pin No.	Signal	Pin No.	Signal
1	GND	12	TXOUT2+	23	TXOUT0B-
2	GND	13	GND	24	TXOUT0B+
3	TXOUT-	14	GND	25	
4	TXOUT+	15	TXOUTCLK-	26	GND
5	GND	16	TXCLKOUT+	27	SCL_G
6	GND	17		28	GND
7	TXOUT-	18		29	SDA_G
8	TXOUT+	19	TXOUT3-	30	GND
9		20	TXOUT3+	31	
10		21		32	GND
11	TXOUT2-	22		33	GND


② CN804-1(Main SMPS) ↔ CN102(Main Board)	
Pin No.	Signal
1	5.3V
2	RTN
3	N/C
4	N/C
5	RTN
6	RTN
7	12V
8	PS_ON
9	RTN
10	STBY
11	FAN_ON
12	FAN_D

③ CN803(Main SMPS) ↔ CN101(Main Board)	
Pin No.	Signal
1	6.5V
2	RTN
3	12V
4	RTN
5	18Vamp
6	18Vamp
7	RTN_amp
8	RTN_amp
9	Vt
10	RTN


④ CN740(Main Board) ↔ CN001(Power Button)		⑤ CN501(Main Board) ↔ Speaker Out		⑥ CN741(Main Board) ↔ CN1(Function Board)		⑦ CN1002(Main Board) ↔ CN#1(DTV Board)		⑧ CN1003(Main Board) ↔ CN#2(DTV Board)	
Pin No.	Signal	Pin No.	Signal	Pin No.	Signal	Pin No.	Signal	Pin No.	Signal
1	GND	1	SPK_R+	1	KEY_INPUT1	1	GND	1	CH_START
2	LED	2	SPK_R-	2	KEY_INPUT2	2	D5V	2	CH_VALID
3	ST5V	3	SPK_L+	3	GND	3	GND	3	CH_CLK
4	GND	4	SPK_L-			4	D12V	4	GND
5	KEY_INPUT2					5	GND	5	CH_DATA0
6						6	DTV_Y_G	6	CH_DATA1
7						7	GND	7	CH_DATA2
8	IR_7414					8	DTV_Pb_B	8	CH_DATA3
						9	DTV_Pr_R	9	CH_DATA4
						10	GND	10	CH_DATA5
						11	DTV_RtO	11	CH_DATA6
						12	N/C	12	CH_DATA7
						13	DTV_SPDIF	13	GND
						14	RESET_IN	14	CH_ERROR
						15	N/C	15	CH_RST
						16	N/C	16	GND
						17	GND	17	USB_VCC_CHECK
						18	D5V	18	USBBN
						19	GND	19	USBBP
						20	D12V	20	GND
						21	GND	21	N/C
						22	N/C	22	N/C
						23	N/C	23	TXD
						24	IR_DTV	24	RXD
						25	DTV_CVBS	25	N/C
						26	GND	26	N/C
						27	DTV_LtO	27	N/C
						28	GND	28	N/C
						29	TxD_MICOM	29	GND
						30	RxD_MICOM	30	CH_SCL
						31	N/C	31	CH_SDA
						32	N/C	32	GND

9-2 Power & IR Board

No	Loc. No.	Description
①	RM1	Remote Control Sensor
②	SW1	Power Button
③	OP1	The Illumination sensor that senses the quantity of light. It senses the illumination and automatically adjusts the screen brightness according to the surrounding brightness when the Power Saving Mode of the User menu is set to Auto.




9-3 Function Board




Function Key. Located on the side of the unit.

9-4 Side AV Board

No	Loc. No.	Description
①	CN102	S-VIDEO2 Input Jack
②	CN103	AV2 Input Jack
③	CN104	Earphone Jack
④	CN105	Side AV Connector



9-5 Main SMPS Board




① CN800 : AC IN (90 ~ 264V)

② CN804-1(Main SMPS) ↔ CN102(Main Board)		③ CN803(Main SMPS) ↔ CN101(Main Board)		④ CN810(Main SMPS) ↔ CN2013(Logic Board)		⑤ CN809(Main SMPS) ↔ CN3(DC-DC SMPS)	
Pin No.	Signal	Pin No.	Signal	Pin No.	Signal	Pin No.	Signal
1	5.3V	1	6.5V	1	STBY	1	5.3V
2	RTN	2	RTN	2	VS_ON	2	Vg
3	N/C	3	12V	3	N/C	3	RTN
4	N/C	4	RTN	4	PS_ON	4	RTN
5	RTN	5	18Vamp	5	RTN	5	RTN
6	RTN	6	18Vamp	6	5.3V	6	RTN
7	12V	7	RTN_amp	7	RTN	7	RTN
8	PS_ON	8	RTN_amp	8	RTN	8	Va
9	RTN	9	Vt	9	5.3V	9	Va
10	STBY	10	RTN	10	5.3V	10	N/C
11	FAN_ON					11	Vs
12	FAN_D					12	Vs

※ CN811, CN804-2 and CN805, CN806, CN807, CN808 are not used.

9-6 DC-DC SMPS Board




① CN809(Main SMPS) ↔ CN3(DC-DC SMPS)		② CN2(DC-DC SMPS) ↔ CN5007(Y SMPS)		③ CN4(DC-DC SMPS) ↔ CN4001(X SMPS)		④ CN1 : N/A ⑤ CN5(DC-DC SMPS) ↔ CN2509(E-Buffer)	
Pin No.	Signal	Pin No.	Signal	Pin No.	Signal	Pin No.	Signal
1	5.3V	1	5.3V	1	Vs	1	RTN
2	Vg	2	Vg	2	Vs	2	N/C
3	RTN	3	RTN	3	RTN	3	5.3V
4	RTN	4	Vscan	4	RTN	4	N/C
5	RTN	5	RTN	5	Ve	5	Va
6	RTN	6	Vset	6	RTN		
7	RTN	7	RTN	7	RTN		
8	Va	8	RTN	8	Vg		
9	Va	9	Vs	9	5.3V		
10	N/C	10	Vs				
11	Vs						
12	Vs						

⑥ D5.3V, Vg, Ve Test Point

⑦ Va, Vset, Vscan Test Point

9-7 PDP Module

※ The ASS'Y code can be changed, see "5 Chapter. Electrical Part List."



No	Assy	Code No.	Description
①	ASSY PDP MODULE P-LOGIC MAIN BOARD	BN96-03355A	Logic Main Board
②	ASSY PDP MODULE P-X MAIN BOARD	BN96-03350A	X Drive Board
③	ASSY PDP MODULE P-Y MAIN BOARD	BN96-03351A	Y Drive Board
④	ASSY PDP MODULE P-Y MAIN SCAN BUFFER	BN96-03352A	Y Buffer Board
⑤	ASSY PDP MODULE P-ADDRESS E BUFFER	BN96-03353A	Address Buffer Board
⑥	ASSY PDP MODULE P-ADDRESS F BUFFER	BN96-03354A	Address Buffer Board


MEMO

10. Schematic Diagram

10-1 Analog


10-1-1 POWER

This Document can not be used without Samsung's authorization.




10-1-2 MICOM

This Document can not be used without Samsung's authorization.




MICOM




10-1-3 IN_OUT_JACK

This Document can not be used without Samsung's authorization.




10-1-5 SOUND


This Document can not be used without Samsung's authorization.

	Power
	Signal

SOUND




SOUND AMP




10-1-7 TUNER

This Document can not be used without Samsung's authorization.





INSERT FOR READY



10-1-12 LVDS

This Document can not be used without Samsung's authorization.


	Power
	Signal




10-1-13 DTV / TUNER / POWER

This Document can not be used without Samsung's authorization.


DTV MODULE CONNECTION




DIGITAL TUNER




PHONE JACK





MODEM JACK



USB




OPTICAL SPDIF OUT



10-12



10-2-2 STi5517 VIDEO / AUDIO / GPIO

This Document can not be used without Samsung's authorization.




10-2-3 MEMORY / EXTERNAL UART

This Document can not be used without Samsung's authorization.




EEPROM_OPTION (2005.10.14)
OPEN EEPROM_OPTION



9P_DSub => Phone Jack (2005.10.14)

10-2-4 INTERNAL CI INTERFACE

This Document can not be used without Samsung's authorization.






11. Operation Instruction & Installation

11-1 Product Features and Functions

11-1-1 Front (or Side) Panel




- 1 **SOURCE**
Displays a menu of all of the available input sources (TV, Ext.1, Ext.2, AV, S-Video, Component, PC, HDMI, DTV).
- 2 **MENU**
Press to see the on-screen menu of your TV's features.
- 3 **- +**
Press to decrease or increase the volume.
In the on-screen menu, use the **- +** buttons as you use the **◀ ▶** buttons on the remote control.
- 4 **∨ C/P ∨**
Press to change channels. In the on-screen menu, use the **∨ C/P ∨** buttons as you use the **▲ ▼** buttons on the remote control.
- 5 **↵ (ENTER)**
Press to confirm a selection.
- 6 **⏻ (Power) button**
Press to turn the TV on and off.

Power Indicator
- Power Off: Blue
- Power On: Off

Remote Control Sensor
Aim the remote control towards this spot on the TV.


➤ Press the MENU button once in DTV mode, then the DTV menu is displayed.



- 1 **S-Video or Video / Audio L/R**
- Video (S-Video or Video) and audio inputs for external devices, such as a camcorder or VCR.
- 2 **headphones jack**
- You can connect a set of headphones to your television if you wish to watch a television programme without disturbing the other people in the room.

➤ Prolonged use of headphones at a high volume may damage your hearing.

11-1-2 Rear Panel



- ☛ Whenever you connect an audio or video system to your set, ensure that all elements are switched off.
- ☛ When connecting an external device, match the colour of the connection terminal to the cable.

- 1 Common Interface Slot
 - Insert CI (Common Interface) card into the slot.
- 2 ANT IN VHF/UHF (75Ω)
 - 75Ω Coaxial connector for Aerial/Cable Network.
- 3 Connecting external Audio Devices
 - Connect RCA audio signals from the TV to an external source, such as Audio equipment.
- 4 DIGITAL AUDIO OUT (OPTICAL)
 - Connect to a Digital Audio Component.
- 5 DTV SERVICE
 - Connector for service only.
- 6 COMPONENT IN
 - Video (Y/P_b/P_r) and audio (AUDIO L/R) inputs for Component.
- 7 PC IN / AUDIO
 - Connect to the video and audio output jack on your PC.
- 8 EXT 1, EXT 2
 - Inputs or outputs for external devices, such as VCR, DVD, video game device or video disc players.

Input/Output Specification

Connector	Input				Output
	Video	Audio (L/R)	S-Video	RGB	Video + Audio (L/R)
EXT 1	✓	✓	✓	✓	Only TV or DTV output is available.
EXT 2	✓	✓	✓		Output you can choose.

- 9 HDMI/DVI IN
 - Connect to the HDMI jack of a device with HDMI output. These inputs can also be used as a DVI connection with separate analog audio inputs. An optional HDMI/DVI cable will be necessary to make this connection. When using the optional HDMI/DVI adapter, the DVI analog audio inputs on your TV allow you to receive left and right audio from your DVI device. (Not compatible with PC)
 - When connecting this product via HDMI or DVI to a Set Top Box, DVD Player or Games Console etc, make sure that it has been set to a compatible video output mode as shown in the table below. Failure to observe this may result in picture distortion, image breakup or no picture.
 - Do not attempt to connect the HDMI/DVI connector to a PC or Laptop Graphics Card. (This will result in a blank screen being displayed)

DVI AUDIO IN L/R

- DVI audio outputs for external devices.

- 10 SERVICE
 - Connector for service only.


- 11 POWER IN
 - Connect the supplied power cord.

➤ Supported modes for HDMI/DVI and Component

	480i	480p	576i	576p	720p	1080i
HDMI/DVI 50Hz	X	O	X	O	O	O
HDMI/DVI 60Hz	X	O	X	X	O	O
Component	O	O	O	O	O	O

11-1-3 Remote Control

- | | |
|---|--|
| 1 POWER button
(turns the TV on and off) | 23 Control the cursor in the menu |
| 2 Number buttons for direct
channel access | 24 Use to see information on the
current broadcast |
| 3 One/Two-digit channel
selection | 26 Fastext topic selection |
| 4 Channel control button | 27 Picture size selection |
| 5 Selects the TV and DTV mode
directly | 28 Sound effect selection |
| 6 \oplus Volume increase
\ominus Volume decrease | 29 Digital subtitle display |
| 7 Temporary sound switch-off | 30 TruSurround XT mode button |
| 8 Displays the main on-screen
menu | 31 If your remote control is not
functioning properly, take out
the batteries and press the
reset button for about 2~3
seconds.
Re-insert the batteries and
try using the remote control
again. |
| 9 Electronic Program Guide
(EPG) display | |
| 10 Picture-In-Picture On/Off | |
| 11 Picture effect selection | |
| 12 Picture freeze | |
| 13 Sound mode selection | |
| 14 Remote control setup | |
| 15 Selects a target device to be
controlled by the Samsung
remote control (TV, DVD,
STB, CABLE, VCR) | |
| 16 Available source selection | |
| 17 Previous channel | |
| 18 DTV menu display | |
| 19 Automatic Power-off | |
| 20 VCR/DVD Function
(Rewind, Stop, Play/Pause,
Fast/Forward) | |
| 21 \odot Next channel
\oslash Previous channel | |
| 22 Exit the on-screen menu | |
| | Teletext Functions |
| | 5 Exit from the teletext display
(depending on the model) |
| | 8 Teletext index |
| | 10 Teletext hold |
| | 11 Teletext size selection |
| | 16 Teletext mode selection
(LIST/FLOF) |
| | 17 Teletext sub page |
| | 21 P \odot : Teletext next page
P \oslash : Teletext previous page |
| | 22 Teletext cancel |
| | 24 Teletext reveal |
| | 25 Teletext display/mix both
teletext information and
the normal broadcast |
| | 26 Fastext topic selection |
| | 28 Teletext store |




- The performance of the remote control may be affected by bright light.
- This is a special remote control for the visually impaired, and has Braille points.

11-2 Installation Notes and Precautions

11-2-1 Installation Notes


1. Contact a technician for installing the wall bracket.
2. Samsung Electronics is not responsible for any damages to the product or harm to customers when the installation is done by the customer.
3. This product is for installing on cement walls. The product may not stay in place when installed on plaster or wood.
4. The package contents and parts supplied for the wall mount are subject to change without prior notice.

11-2-2 Mounting Kits




11-2-3 How to assemble the Wall Mount Bracket

- 1 The wall mount bracket is delivered separately. Please tighten the captive screw in the direction of the arrow after assembling the bracket. Install the Wall Mount Bracket after the screws are securely inserted into the wall.




11-2-4 Instructions on Securing the SET to the Wall Mount Bracket

- 1 Remove the screws from the back of the PDP.




- 2 Use the screw and assemble the plastic hanger. (Please refer to the following picture.)




- 1 Please ask the installers to install the wall mount bracket.
 2 Please be sure to check if the plastic hanger is completely secured on both the left and right side after hanging the SET on the wall mount bracket.
 3 Please avoid catching your fingers while installing and adjusting the angle.
 4 Please tightly secure the wall mount bracket to the wall to avoid injury from a falling SET.


- 3 Tighten the screws of the plastic hanger (shown in picture 2) to the back side of the PDP.




- 4 Remove the Safety Pins. Fasten the 4 plastic latches assembled at step (3) on the back side of the PDP using the guide holes of the wall mount, push (1) and hook (2) down to secure the PDP on the wall mount as illustrated. Secure the PDP by inserting the Safety Pins, not to fall from the wall mount.



11-2-5 How to Adjust Mounting Angle




- 1 Secure the SET to the wall mount bracket.(Please refer to the following instructions.)
- 2 Set the angle by pulling the upper end of the SET attached to bracket in the direction of the arrow. (Refer to the illustration on the right.)
- 3 The angle can be adjusted from 0° to 15° by $\pm 2^\circ$.



Hold onto the middle of the PDP to adjust the angle (not the sides of the PDP).

11-2-6 Connecting External Devices to the PDP



- 1 Be sure to remove the safety pins underneath the PDP.
 - If the safety pins are not removed, the angle cannot be adjusted. Any attempt to do so may cause damage to the PDP.
- 2 Hold onto the bottom of the PDP and pull forward fully as directed by the arrow as illustrated) to adjust the angle. (0°~20° by 2°) Insert the Safety Pins to the front guide holes on both sides as illustrated in figure ②.
 - Viewing the PDP after connecting the external devices Remove the Safety Pins to adjust the angle to 0°, and then secure the Safety Pins again.
 - ☞ For safety, be sure to secure the PDP using the safety pins. If the safety pins are not used, the PDP may fall, causing serious injury.


12. Disassembly & Reassembly

12-1 Overhaul Disassembly & Reassembly


△ Notice

- Be sure to separate the power cord before disassembling the unit.
- Discharge the capacitors first when separating PCB's with high capacity capacitors such as SMPS, X Main Board, Y Main Board, etc. (A spark may be generated by the electric charge, and there is danger of electronic shock.)
- Check that the cables are properly connected referring to the circuit diagram when disassembling or assembling the unit taking care not to damage the cables.
- Take care not to cause a flaw in the Glass Filter in the front.
- Assemble the boards in the reverse order of the disassembly.
- The plasma must be laid down on a flat padded surface for disassembly and reassembly.


12-1-1 Separation of ASSY STAND P-BASE

Part Name	Description	Description Photo
Stand	<p>① Remove 4 screws. : PH,+,WSP,S,M4,L35,ZPC(BLK)</p> <p>② Pull the ASSY STAND P-BASE down to remove it from the unit.</p> <p>△: Please lay the PDP unit face down on a soft surface when removing the stand.</p>	


12-1-2 Separation of ASSY COVER P-REAR

Part Name	Description	Description Photo
Cover Rear	<p>① Remove 4 screws.(□) : M8,L16,ZPC(BLK),SWRCH18A,WP</p> <p>② Remove 14 screws.(○) : BH,+,B,M4,L12,ZPC(BLK)</p> <p>③ Remove 4 screws.(●) : BH,+,S,M4,L10,ZPC(BLK)</p> <p>④ Remove the ASSY COVER REAR.</p>	


12-1-3 Separation of ASSY BRACKET P-TERMINAL

Part Name	Description	Description Photo
Bracket Terminal	<ol style="list-style-type: none"> ① Remove the 2 Hex nuts for the PC input. : #4-40,L6,NI PLT,C3601,- ② Remove Bracket Terminal. 	


12-1-4 Separation of ASSY PCB MISC-MAIN & DTV MODULE

Part Name	Description	Description Photo
Main & DTV Module Board	<ol style="list-style-type: none"> ① Detach all connectors from the Main Board. ② Remove 7 screws. : PH,+,WWP,M3,L8,NI PLT ③ Remove the Main Board. 	


12-1-5 Separation of BRACKET-PCB

Part Name	Description	Description Photo
Bracket PCB	<ol style="list-style-type: none"> ① Remove 3 screws. : BH,+,S,M4,L10,ZPC(BLK) ② Remove the BRACKET-PCB. 	


12-1-6 Separation of FILTER-EMI AC LINE

Part Name	Description	Description Photo
FILTER EMI AC LINE	<ol style="list-style-type: none"> ① Detach connector from Main SMPS. ② Remove 2 screws. : PH,+,WWP,M3,L8,NI PLT ③ Remove a screw. : BH,+,S,M4,L10,ZPC(BLK) ④ Remove FILTER-EMI AC LINE. 	


12-1-7 Separation of ASSY BOARD P-SIDE AV

Part Name	Description	Description Photo
Side AV	<ol style="list-style-type: none"> ① Remove 1 screw. : BH,+,S,M4,L10,ZPC(BLK) ② Remove the Side AV assy. 	


12-1-8 Separation of SHIELD CASE

Part Name	Description	Description Photo
Shield Case	<ol style="list-style-type: none"> ① Remove 2 screw. : BH,+,S,M4,L10,ZPC(BLK) ② Remove the Shield Case. 	


12-1-9 Separation of ASSY BRACKET P-WALL

Part Name	Description	Description Photo
Wall Bracket	<p>① Remove 8 screws. : BH,+,B,M4,L12,ZPC(BLK)</p> <p>② Remove 8 screws. : BH,+,S,M4,L10,ZPC(BLK)</p> <p>③ Remove Wall Bracket.</p> <p>⚠: Please lay the PDP panel face down on a soft surface when separating front cover.</p>	


12-1-10 Separation of ASSY SPEAKER P

Part Name	Description	Description Photo
Speaker	<p>① Remove 4 screws. : BH,+,WP,B,M4.0,L12,ZPC(BLK),SWRCH18A,-</p> <p>② Remove the Speaker.</p>	


12-1-11 Separation of ASSY BOARD P-POWER&IR

Part Name	Description	Description Photo
Power & IR Board	<p>① Remove 2 screw. : BH,+, -,S,M4,L8,ZPC(BLK)</p> <p>② Remove the Power & IR Board.</p>	



12-1-12 Separation of ASSY PCB P-SMPS & SMPS DC-DC

Part Name	Description	Description Photo
SMPS & SMPS DC-DC Board	<ol style="list-style-type: none"> ① Detach all connectors from the Assy PCB P-SMPS. ② Remove 8 screws. : PH,+,WWP,M3,L8,NI PLT ③ Remove the Assy SMPS PCB. ④ Detach all connectors from the Assy SMPS DC/DC Board. ⑤ Remove 4 screws. : PH,+,WWP,M3,L8,NI PLT ⑥ Remove the SMPS DC/DC Board. <p>⚠ : Wear gloves when handling the power board as there may be some remaining electrical charge in the capacitor. Specifically, avoid touching any part of the capacitor.</p>	





12-1-13 Separation of ASSY PDP MODULE P-LOGIC MAIN BOARD


Part Name	Description	Description Photo
Logic Board	<ol style="list-style-type: none"> ① Detach all connectors from the Logic Main Board. ② Remove 4 screws. : WSP,PH,+,M3,L8,NI PLT ③ Remove the Logic Main Board. 	

12-1-14 Separation of ASSY PDP MODULE P-X MAIN BOARD



Part Name	Description	Description Photo
Flat Cable	<p>① Detach all Connectors from the X Main Board.</p> <p>※ To separate the Flat Cable of the X-Board, press the upper and the lower sides of the connector.</p>	
X-Main Board	<p>① Remove 4 screws. : PH,+,WWP,M3,L8,NI PLT</p> <p>② Remove the X-Main Board.</p>	

12-1-15 Separation of ASSY PDP MODULE P-Y MAIN BOARD

Part Name	Description	Description Photo
Flat Cable	① Detach the 6 scan board connectors from the panel by pulling the holder from both the top and bottom ends.	 
Y-Scan	① Remove 2 screws. : PH,+,WWP,M3,L8,NI PLT	
Connectors	① Separate the scan board from the Y-Main Board by detaching the 3 connectors and remove the Scan Boards.	

Part Name	Description	Description Photo
Y-Main Board	<p>① Remove 4 screws. : PH,+,WWP,M3,L8,NI PLT</p> <p>② Detach all connectors from the Y-Main Board.</p>	


12-1-16 Separation of ASSY PDP MODULE P-ADDRESS BUFFER BOARD

Part Name	Description	Description Photo
Still Bar	<ol style="list-style-type: none"> ① Remove 3 screws. : PH,+,WWP,M3,L8,NI PLT ② Remove the still bar. 	
Buffer	<ol style="list-style-type: none"> ① Detach the all connectors from the buffer board. ② Remove 10 screws. : PH,+,WWP,M3,L8,NI PLT ③ Remove the E-Board and F-Board. 	

MEMO

13. Circuit Description

13-1 Power ON/OFF Signal Timing Sequence



1. When connecting the AC power cord, Stand-By 5V from the Main SMPS is supplied to the Main Board (Pin 3 of CN1002 of Main Board).
2. When pressing the Power button on the remote control or on the main body, PS_ON (Pin 5 of CN1002 of Main Board) changes from High to Low.
3. If the PS_ON signal changes to Low, the Main SMPS supplies power to the Main Board and Logic Board, and Va and Vg power is supplied to the DC-DC SMPS.
4. If the VS_ON signal from the Logic Board changes from Low to High, the Main SMPS supplies VS power to the X and Y Main Board through the DC-DC SMPS, and the screen displays a picture on it.

13-2 Partial Block Description

13-2-1 Main SMPS

1. Outline (PDP 42inch/50inch SMPS)

Considering various related conditions, the switching regulator with good efficiency and allowing for its small size and light weight was used as the power supply for PDP 42inch/50inch, VS requiring high power consumption Asymmetrical Half Bridge converter and flyback converter. To comply with the international harmonics standards and improve the power factor, active PFC(Power Factor Correction) was used to rectify AC input into +400V DC output, which in turns used as input to the switching regulator.

2. Input

The power supply shall be capable of supplying full rated output power over free voltage ranges that are rated 100 VAC - 240 VAC RMS nominal. Operating voltage : 90 VAC - 264 VAC

The power supply must be able to start up under peak loading at 90V AC. The power supply shall automatically recover from AC power loss. (Note that nominal voltages for test purposes are considered to be with +/- 1.0V of nominal).

STD_5V & Vpr2(3.3V) is a SELV standby voltage that is always present when AC mains voltage present.

3. Output

Output Name	Output Voltage	Output Current(Max.)	Using in PDP Driving
VS	+190V ~ 220V (210V)	2.0A	Sustain Voltage of Drive Board
VA	+60V ~ 80V (70V)	3.0A	Address Voltage of Drive Board
D5.3V	+5.3V	5.0A	
A6.5V	+6.5V	3.0A	
FAN_9V	+9V	0.2A	
VG	+15V	1.0A	
D12V	+12V	1.5A	
A12V	+5.3V	0.5A	
18VAMP	+18V	2.5A	Amp Voltage of Audio Board
VT	+33V	0.006A	
STD_5V	+5V	1.0A	Standby for Remote Control

① Over Voltage Protection

The over voltage sense circuitry and reference shall reside in package that are separate and distinct from the regulator control circuitry and reference. No single point fault shall be able to cause a sustained over voltage condition on any of all outputs.

The supply shall provide latch-mode Over Voltage Protection as defined below.

Parameter	Min	Unit
VS(210V)	250 ~	V
VA(70V)	100 ~	V
VCC(+5.3V)	6.8 ~	V

② Short Circuit and Over current Protection


An output short circuit is defined as output impedance of less than 300mohms. The power supply shall shutdown and latch off for shorting VS DC rails to return. Shorts between main output rails and STD_5V shall not cause any damages to the power supply. The power supply shall either shutdown and latch off for shorting is removed, the P/S shall recover. The power supply shall be capable of withstanding a continuous short-circuit to the output without damage or over stress to the unit (components, PCB traces,connectors,etc.) under the input conditions specified in Section 3 above. Current Protection as defined below.

Output	Over Current Limit	Unit
VS(210V)	20A, Constant Current.(TBD)	A
VA(70V)	10A, Constant Current.(TBD)	A
Output except Vs,Va	No damage (Auto Recovery or Shut down.)	A

13-2-2 PDP Module

1. Logic Board

■ A name of main part of Logic Board and vocabulary.



Item	Name	Explanation												
①	Y Connector	The connector to output the control signal for the Y drive board.												
②	LVDS Connector	The connector to receive the RGB, H, V, DATAEN and DCLK signals that have been LVDS encoded through the Main board.												
③	Power Connector	The connector to receive power (5V, 3.3V) for the Logic board.												
④	X Connector	The connector to output the control signal for the X drive board.												
⑤	ASIC CHIP	The main processor that generates and outputs the logic drive signal and the address data.												
⑥	DDR MEMORY (MENCON)	The Memory to restore Address output data.												
⑦	DDR MEMORY (Frame Delay)	The Memory to restore FCR data.												
⑧	JTAG PORT	The port to communicate uCOM.												
⑨	Initial image option PIN	Initial image select F/W or BLACK : Jumper Yes : <table><tr><td>4</td><td>3</td></tr><tr><td>2</td><td>1</td></tr></table> or <table><tr><td>4</td><td>3</td></tr><tr><td>2</td><td>1</td></tr></table> Full White, Jumper No : <table><tr><td>4</td><td>3</td></tr><tr><td>2</td><td>1</td></tr></table> Black	4	3	2	1	4	3	2	1	4	3	2	1
4	3													
2	1													
4	3													
2	1													
4	3													
2	1													
⑩	Micom Loading 5Pin Connector or Uart Connector	The connector to load the Micom drive program. The program is loaded by connecting to the GA-WRITER. Connector that loads and controls 512K data, and connects kiss can Board												
⑪	ARM-PROCESSOR	IC block Control-signal to drive logic main.												
⑫	Buffer Connector	The connector to output the address data and the control signal to the E-buffer board.												
⑬	Operating Status LED	The LED that shows whether the Sync and Clock signal is properly supplied to the logic board. (Normal Status: Blinks at 0.5 second intervals)												
⑭	Buffer Connector	The connector to output the address data and the control signal to the F-buffer board.												
⑮	V-TOGG	V-SYNC output pin.												

■ About Logic Board

The Logic Board consists of a Logic Main board, which processes the video signal input through LVDS and creates the address driver output and XY drive signals, and a Buffer board, which buffers the output signal and outputs the signal to the Address Driver IC (TCP IC).


Logic Board		Function	Remark
Logic Main		<ul style="list-style-type: none"> - Video Signal Processing (W/L, error diffusion, APC, FCR) Built-in LVDS Application and 1 ASIC Chip - Outputs the Address Driver Control and Data Signals to the Buffer board - Outputs the XY Drive Board Control Signal - Major Drive Voltage Monitoring (MICOM Circuit Block) : Detects abnormal voltage applications and protects drive circuits - Temperature Induced Operating Mode (Low Temperature/Room Temperature/High Temperature) : Optimization of discharge by temperature 	
Buffer Board	E Buffer Board	Outputs data and control signals to the bottom left TCP IC.	Single Scan
	F Buffer Board	Outputs data and control signals to the bottom right TCP IC.	

■ Normal Waveform


When the Operating LED blinks normally (at 0.5 second intervals), which indicates the normal operation of the PDP Set and Logic Board, and the V-SYNC and data output signals are normal.

If the set is out of order, perform troubleshooting according to the procedures below.

- 1) Visual Inspection : Check if the Operating LED on the Logic Main blinks at a 0.5 second interval.
 - ▶ If the Operating LED blinks too fast or too slow, you have to reload the data onto the MICOM, as this indicates abnormal data processing in the MICOM. To load the data, supply power to the module and load the data using GA-WRITER.
- 2) If no problem has been found through the visual inspection, check if the drive waveforms and the address data output are normal. (Check Point: Check the DAMPING R-NET output of each data output terminal.)
 - ▶ If no drive waveform or address output signal is detected, load data onto the MICOM according to the procedures described above, as this indicates a MICOM data error.
 - ▶ If data output is detected but is abnormal, it indicates a hardware short-circuit if measured for the drive waveform, or it indicates abnormal data output due to the abnormal operation of the DDR memory caused by the abnormal Vref voltage if measured in the address data. Abnormal data output due to the abnormal operation of the DDR memory or a short circuit on the board, which may be caused during the ass'y process, causes the screen to be abnormally displayed. Therefore, you have to conduct a short test for each part.
 - ▶ If the Vref voltage (Voltage Divider Voltage) is lower than 1.25V, check the resistance of the resistance output part and check if the circuit status is normal. This applies the voltage and the proper Vref voltage and results in the screen being properly displayed.
 - ▶ If the screen is abnormally displayed, even though the Vref voltage is normal, find any abnormal points by conducting a short test. If a short circuit is found and it is repairable, repair it. If a short circuit is internal, replace the board.
 - ▶ The following waveform appears when the V-sync and address data are output properly.



< Normal V-SYNC Output Waveform >



< Normal Address Data Output Waveform >

2. X, Y Control Block

■ Drive Circuit Definition

The Drive Circuit is a circuit that generates a waveform (high-voltage pulse) for the X and Y electrode group of the panel's external port so as to control the panel. The high-voltage switching pulse is generated through the combination of the IC HYBRID (Drive block + IGBT) and FET.

■ Drive Circuit Mechanism

A picture is displayed on the PDP by applying voltage to the X, Y and ADDRESS electrodes of each pixel according to the appropriate condition. The drive waveform applied to 42HD V4 is of the ISSS (ISSS: Interweaving Scan and Selective Sustain with Scan IC) type and has IDS (InDependent Sustain) in the Scan section unlike the existing ADS. Discharges within a PDP pixel can be classified into 3 types:

- ① Address Discharge: To form a wall voltage within the pixel by giving information (applying DATA voltage) to the pixel to be lit.
- ② Sustain Discharge: Sustain Discharge is a display section that voluntarily maintains the discharge of the pixels whose wall voltage has been formed by the Address Discharge. (Optical output for displaying a picture is generated).
- ③ Erase Discharge: To selectively perform Address Discharge for each pixel, all pixels on the panel should be in the same status (the wall electric charge status and space electric charge status must be the same). Therefore, the Erase Discharge section is an important component for guaranteeing the drive margin, and is implemented by various methods such as applying a log waveform. However, the current 42HD V4 has adopted a wall voltage control through an RA (Repeated Auto-quenching) reset that separates the discharge area and performs switching to perform an efficient erase operation, while the gradient was the same in the RAMP section in the existing approach.

1) Address Discharge

A discharge that is caused by the difference between the plus electric potential (V_a apply voltage of 65~70V + Positive Wall Charge) of the electrode and the negative electric potential (Applied GND Level + Negative Wall Charge) of the Y electrode. The Address discharge forms a wall voltage within the pixel to display color (to be discharged) before the Sustain Discharge period. That is, the pixel whose wall charge has been formed by the Address Discharge forms a Sustain Discharge via the following Sustain pulse.

2) Sustain Discharge

A Sustain Discharge is a Self-Sustaining Discharge formed by the accumulation of the electric potential of the Sustain pulse (generally 200 ~ 210 Volt) alternating over the X and Y electrodes during the sustain period, and the wall charge depending on whether the pixel has previously been discharged or not. That is, it is controlled by the memory characteristics, one of the basic characteristics of the AC PDP (in that the past operating conditions determine the current status). That is, if a wall voltage exists on the pixel (if the pixel is on), a discharge is formed again because the applied voltage, which is the sum of the following applied Sustain voltage and the wall voltage, is higher than the discharge threshold voltage. If no wall voltage exists on the pixel (if the pixel is off), a discharge will not occur because the Sustain voltage is not higher than the discharge threshold voltage. The Sustain Discharge period is the period for generating actual optical output so as to display a picture on the PDP screen.

3) Erase Discharge

The purpose of a Reset (Erase) Discharge is to create uniformity of the wall voltage within all panel pixels. It evens the wall voltages regardless of the Sustain Discharge in the previous stage. The Erase Discharge has to remove the wall voltage introduced by the Sustain Discharge by supplying ions or electrons by a discharge. When the wall voltage is removed through a discharge, the time when the reverse polarity is applied to the wall voltage (fine width erasing) is to be limited or ions or electrons are to be supplied by a weak discharge (low voltage erasing) so as to prevent a wall charge in reverse polarity.

There are 2 known weak discharge (low-voltage) erase methods. 1) A log waveform adopted by F company and 2) a weak erase discharge via a ramp waveform adopted by Matsushita and other companies. Both methods control the externally applied voltage by the difference of the wall voltage of the pixel by applying the rising gradient of the erasing waveform slowly, because the discharge begins when the sum of the existing remaining wall voltage and the rising waveform voltage exceeds the drive threshold voltage. In addition, a weak discharge is introduced, because the applied voltage is low.

■ Requisite Components Necessary for Drive Board Operation

1) Power


- Supplied from the power board. The optimal value may differ from the following:
 - a) V_s : 200V - Sustain
 - b) V_{set} : 190V - Y Rising Ramp
 - c) V_e : 110V - V_e bias
 - d) V_{scan} : -190V - Scan low bias
 - e) V_{sc_h} : -70V - Scan high bias (Created by the DC-DC power block of the Y Drive board)
 - f) V_{dd} : 5V - Logic signal buffer IC
 - g) V_{cc} : 15V - Gate drive IC

2) Logic Signal

- Supplied by the Logic board
- Gate signal of each switch

■ Drive Circuit Architecture and Function Description

- Description of the function of each board



1) X Drive Board

This is connected to the X port part of the panel. 1) Sustain voltage waveform (including ERC) is output, and 2) V_e bias in the Scan section is maintained.

2) Y Drive Board


This is connected to the Y port part of the panel. It outputs 1) Sustain voltage waveform (including ERC), and 2) Y Rising, Falling Ramp waveform, and maintains 3) V_{scan} bias.

3) Y Buffer Board

A board, which applies the Scan waveform to the Y terminal block, consists of 12 Scan Driver ICs (TI SN755870: 64 Outputs).

■ Drive Waveform Specifications

- Drive Waveform



- Description of the function of each pulse

1) Y Preset RA Pulse

This is supplied to the first sub-field and erases the discharge status of the previous subfield.

2) Y Main RA Pulse

During the Y Rising Ramp section, approximately 300V~350V ($V_{scan-h} + V_{set}$) of external voltage is supplied to the Y electrode, and a weak discharge is started when each gap voltage is equal to the discharge start voltage. While maintaining the weak discharge, as a whole, negative wall charges are accumulated on the Y electrode and positive wall charges on the X electrode and the address electrode.

During the Y Falling Ramp section, the negative wall charges accumulated on the Y electrode by the approximately 105V of X bias are used to erase the positive wall charges on the X electrode, and the address electrode maintains most of the positive wall charges accumulated during the (0V) Rising Ramp section preparing for the next address discharge.

3) Y Scan Pulse (Odd/Even)

A scan pulse classifies the Y electrode into Odd and Even lines and selects FPC output electrodes sequentially (one line-at-a-time). At this time, V_{scan} is called the Scan Bias Voltage.

A V_{scan} voltage of approximately -175 Volt (V_{sc-1}) is supplied to the electrode lines. For the other lines, -56 volt (V_{sc-h} is higher than V_{sc-l} by 120V) is supplied. However, negative wall charges are accumulated on the Y electrode by the Ramp pulse, and positive wall charges are accumulated on the address electrode, and the voltage applied to the cells, to which the Address pulse (70V~75V) has been applied, becomes higher than the discharge voltage. An address Discharge occurs as a result. Since the Scan and Data pulse is applied one line at a time as above, the address time of PDP is very long.

4) IDS Pulse (InDependent Sustain Pulse)

Since an Odd Scan is performed first, the Odd line output sustains optical twice during the IDS section. At this time, a Sustain Discharge does not occur for the Even line because the Even line is not scanned.

5) CPS Pulse (ComPare Sustain Pulse)


By floating the Odd line that caused the Sustain Discharge in the IDS section to the V_{scan-h} level, and introducing the Sustain Discharge only for Even lines, it compensates for the optical output difference between the Even and Odd lines.

6) CMS Pulse (ComMon Sustain Pulse)

Actual optical is output during the common Sustain Discharge section.

■ Mechanism of the FET Operation and High-Voltage Switching


Mechanism of the FET Operation



G : Gate
S : Source
D : Drain


- 1) When the signal is output to the gate, (positive electric potential) FET short circuits (i.e. Conductor of resistance 0)
- 2) When no signal is output to the gate (GND), FET changes to an open circuit (i.e. an insulator of resistance ∞).

High-Voltage Switching of the FET Operation




- 1) When no signal is applied to G1, FET1 is opened and when the signal is applied to G2, FET2 short circuits, GND is output via the output terminal.
- 2) When a signal is applied to G1, FET1 short circuits and when no signal is applied to G2, FET2 is opened, and 180V is output via the output terminal.



■ Drive Board Connector Layout
1) X-Main Board



2) Y-Main Board



- Adjust the drive waveform so that the main reset (rising, falling:40usec) is the same as those in the F/W pattern.
(※ Attachment 1 reference)




< Y-Main >

<Voltage Adjustment Specifications>


Vset	Vs	Vsc_l	Vsc_h	Ve	Va
195V	200V	-190V	-70V	120V	65V

- Check that the output of X-Out of the X board follows the waveform of ※ Attachment 2 when the power is supplied.




※ Attachment 1

■ Y Output Waveform





< Rising Ramp >




Falling Ramp

< Falling Ramp >



※ Attachment 2

■ X Output Waveform



< X Sustain >

14. Reference Information

14-1 Other issues related to other products

Problem	Descriptions
A fixed screen can cause permanent damage to the TV Braun tube.	Braun, PDP and LCD TVs can all be damaged. When a still image is displayed in a sequence, this can leave stains or after-images due to the characteristics of the panel. However, the DLP TV has the advantage that no stains or after-images are left on the screen. The DLP TV has mirror pixels on the DMD panel that project the beam onto the screen, in which the mirror is a digital representation of 0s and 1s, leaving no trace of light. The mirror returns to a blank state so that no stains or after-images are left.
Length of DVI Cable / PC RGB Cable	- A too long DVI cable may cause a malfunction or degradation of the visual quality due to an attenuation of the signal. There is no recommendation for the cable length at present. In general, although a cable length of up to 5 meters should work, please check if video is properly displayed on the screen after connecting. If you think the length of the cable is longer than for normal use, check the visual quality of the video on the screen and shorten the length, if necessary. - This also applies to the PC RGB (D-Sub) cable. When the length of the cable is longer than for normal use, video may not be displayed on the screen. In this case, shorten the cable length.
When a digitally distributed TV user receives HD-rated broadcasts:	The digital distributed TV (Ready Technique) can render HD sources as HD-rated. However, you need to install a set-top box for this purpose. The digital TV alone cannot render HD broadcasting as HD-rated. Install the formal set-top box for HD broadcasts.
When a digital distributed TV user selects normal size (4:3) to receive SD-rated digital broadcasts:	The digitally distributed TV (Ready Technique) renders any broadcasting service as SD-rated. However, when connected to a set-top box, the digital TV renders HD broadcasts as HD-rated and renders SD as SD-rated. The screen size is scaled to 4:3.
When a digitally built-in TV user receives SD (air) broadcasting:	The digitally integrated TV ("built-in" type) renders SD broadcasting as SD-rated. This can be understood easily. Even a high-resolution TV cannot improve a low resolution picture into high quality. In contrast, an SD-rated TV cannot represent HD broadcasting as HD because the resolution of the TV is lower than the original.
When selecting a picture size of 4:3 in connection with a computer or a multimedia device:	The representation capability of SD or HD-rated depend entirely on the TV set. The HD TV can render HD broadcasting as HD-rated only when it receives HD sources. In the meantime, the HD TV renders SD as SD-rated when it receives SD sources. The picture size has nothing to do with the resolution; TV models like SVP-XXL3HD or SVP-XXL6HD have a size adjustment feature to 16:9, 4:3, Panorama, Zoom1, Zoom2 and Auto Wide. This is about the aspect ratio of the top and bottom boundaries to the overall screen and users can select their preference.

■ SD/HD broadcasts and the TV's display capability are related

1. A digital broadcast should be transmitted in wide screen (an aspect ratio of 16:9) HD. If the broadcasting station converts a conventional program created in normal screen (aspect ratio of 4:3) into a digital signal and broadcasts the signal, the left and right of the picture will not be displayed.


This symptom also appears in other manufacturer's TV's. The three appliance companies are trying to resolve the problem through the Ministry of Information and Communication.

- * When watching an SD (normal) broadcast through a Digital (Wide) TV (480P normal broadcast)
- * When watching an SD (normal) broadcast through a Digital Ready (Wide) TV (Using a set-top-box)
- * When watching an analog (normal) broadcast through a wide TV
(When watching a broadcast after changing the aspect ratio of the TV from 16:9 (wide screen) to 4:3)

2. When watching a DVD title or video tape in wide screen (21:9) through a wide (16:9) TV, watching video from a computer or game console by selecting the aspect ratio to 4:3, or watching video from a DVD, VCR, computer or game console through a wide TV by selecting the aspect ratio to normal (4:3) or wide (21:9), the left and right, or top and bottom of the picture will not be displayed.

This symptom appears in other manufacturer's TV's. The three appliance companies are trying to resolve the problem through the Ministry of Information and Communication.

■ Changing the Order of the Picture Size for 16:9 Display Devices



■ Changing the Order of the Picture Size for DTV 1080i/720p Sources



■ Restrictions

1. When you want to change the picture size in PIP 'ON', you must turn the PIP off before changing the size. However, you can change the main picture size even in PIP ON for products with no restrictions.
2. When the picture size is not Normal (4:3 for 4:3 display devices, 16:9 for 16:9 display devices) and you turn PIP on, the picture size is changed to Normal. However, you can turn PIP on without changing the picture size for products with no restrictions.
3. In the OSD notation for the picture size, 16:9 is represented as "Wide" instead of "16:9" for devices other than with 16:9 displays.
Ex: For LCD 15:9 devices, "Wide" is displayed on the OSD instead of "16:9".
4. The picture size can be changed even in the blue screen. However, the picture size should be controlled by the product specifications if the change is impossible due to hardware restrictions.

14-2 Technical Terms

Virtual Channel

In digital channels, a virtual channel is used. A virtual channel is a function that enables users to watch a channel by selecting a virtual channel number regardless of the region of the user. Run Auto Channel Scan for digital broadcasts, tune in to a UHF channel number according to the region for terrestrial broadcasts, or tune into a channel number allocated by the cable broadcasting station for a cable TV network, and then select a displayed virtual channel.

For example, even if you tune into channels UHF 14(MBC), 15(KBS1), 16(SBS), 17(KBS2) and 18(EBS) broadcast from Kwanak mountain in Seoul, you can watch the channels using virtual channels such as 11-1(MBC), 9-1(KBS1), 6-1(SBS), 7-1(KBS2) and 10-1(EBS) regardless of your region and the actual local channel number. The virtual channel numbers may be used nationwide, but the virtual channel numbers may vary depending on the local broadcasting stations.

(Since the digital channel numbers may vary depending on your region and can be changed by the broadcasting policy, ask your local broadcasting station or regional cable TV network company about the channel numbers.) If the virtual channel numbers are saved and the TV set can receive digital broadcasting, you can watch a digital channel by pressing the DTV+ button and pressing the first two digits of the corresponding virtual channel number.

Custom Color Adjustment

Using this function, a user can adjust the color according to personal preferences (Red, Grass-Color, Sky-Color, Gold-Color, Skin-Color, White, Standard, Custom) without affecting other colors using automatic selection mode or fine adjustment mode.

Simultaneous Screen

Using this function, a user can view two video signals from separate video sources on a single screen at the same time. For example, you can watch TV and video simultaneously.

Dolby Digital

This is the digital sound standard developed by the Dolby Laboratory. You can select your preferred digital surround mode after connecting external speakers.

Digital Broadcasting

Digital Broadcasting is a television broadcasting signal digitized and transmitted according to the United States' terrestrial digital broadcast standard, or ATSC.

Mono

A type of audio interface that transmits the audio signal through a single channel only.

Through a mono interface, it is hard to experience stereophonic sound and the sound is played using only one speaker.

Reception Sensitivity Amplification (LNA)

A signal amplification technique that amplifies a weak broadcasting signal by applying satellite technology to provide better visual quality even for users in regions where only a weak broadcasting signal is available. (LNA: Low Noise Amplifier)

Sub Woofer

A Sub Woofer is a speaker for ultra bass sound output only whose frequency is as low as 150Hz. There are two types: an active type which includes an amplifier, and a passive type, which requires an additional amplifier.

Stereo

A type of audio interface that transmits audio signal through 2 channels.

Stereo transmits audio signals for right and left sound so that you can experience stereophonic sound, and the sound is played through 2 speakers.

Partial Color Blind Person Mode

Using this function, a user can adjust the red, green or blue colors according to the preferences of the partially color-blind person so that he or she can view the clearest possible picture on the screen.

Analog Broadcasting

Analog Broadcasting is a television broadcasting signal transmitted according to the NTSC standard.

ANTENNA IN Port

The port connecting the TV aerial via a coaxial cable. It is generally used for watching public broadcast programs.

English Caption

A function that displays English captions or text information included in the broadcast signal or video tape. You can use this function for your English studies by watching AFKN or CC marked video tapes.

Video/Audio Ports

You may experience poor visual and audio quality when watching a video tape on channel 3 or 4 through the antenna cable. You can experience better visual and audio quality by connecting the TV and VCR through the Video/Audio ports. The video port is in yellow, and the audio ports are in white and red.

Wide Screen

Wide Screen refers to a screen that is horizontally longer than a conventional TV screen.

While the aspect ratio of a normal TV is 4 : 3, that of a wide screen is 16 : 9.

External Input

External Input is a connected video device such as a VCR, camcorder, DTV receiver, DVD, etc. as a video source.

Satellite Broadcasting

Satellite Broadcasting transmits programs via satellite so that a program can be viable in all areas at a high visual and sound quality. Approximately 100 channels including public broadcast channels are provided. To view a satellite broadcast, you have to install an additional receiver.

Wire Broadcasting

Wire Broadcasting refers to movie, entertainment and educational programs transmitted by a broadcasting station within a hotel or school.

Audio Multmix

Audio Multmix provides 2 audio languages when foreign movie, drama, news, etc. are broadcast. You can select and listen to one of the supported languages or you can select and listen to both languages simultaneously.

After-Image Protection

Using this function, a user can configure the options necessary for protecting the PDP TV screen.

Power Saving Mode

This function adjusts the screen brightness according to the ambient brightness so as to conserve power.

Component Port

The Component Port transmits a separate luminance signal as well as the green, blue, and red color signal and provides the best quality of all video connection types.

Cable Broadcasting

Cable Broadcasting transmits programs via cable instead of via the air. To view cable broadcasting, you have to subscribe to your local cable broadcast service provider and install an additional receiver.

Tuner

A device that enables the selecting of specific channel frequencies for TV or radio.

Panorama Screen

This refers to a screen that corrects the picture distortion due to a screen size mismatch on the TV.

Progressive Scan

Progressive scan displays the entire frame in a single sweep so as to provide clearer and sharper visual quality.

DVD (Digital Versatile Disc)

DVD is a large capacity storage media that can store multimedia content such as video, games, audio applications, etc. using MPEG-2 video compression technology on a CD sized disc

DRC

This is a sound quality enhancement function that automatically controls audio output so as to prevent sound quality distortion even at loud volumes and correct the sound to the speakers so that you can listen to the sound at the original sound quality.

DVI (Digital Visual Interface) Port

A DVI interface is a standard for high definition television connectivity. It provides a clear picture on the screen using TMDS which minimizes video signal loss.

DVI-D Cable

A type of DVI connector. Using this cable you can only transmit digital signals.

DVI-I Cable

A type of DVI connector. Using this cable you can transmit either digital or analog signals.

HDMI

HDMI (High-Definition Multimedia Interface) is the first industry-supported, uncompressed, all-digital audio/video interface. HDMI provides an interface between any audio/video source, such as a set-top box, DVD player, and A/V receiver and an audio and/or video monitor, such as a digital television (DTV). HDMI supports standard, enhanced, or high-definition video, plus multi-channel digital audio on a single cable. It transmits all ATSC HDTV standards and supports 8-channel digital audio, with bandwidth to spare to accommodate future enhancements and requirements.

PCM

PCM (Pulse Coded Modulation): This refers to an uncompressed digital signal. Use this for an AV amplifier that does not support 5.1 channels when connecting the audio output via optical or coaxial cable.

SRS TruSurround XT

This function provides 5.1 channel surround sound using 2 channel speakers when inputting a stereo audio signal.

VESA Plug & Play

This function enables the automatic recognition of devices when connecting the TV to the computer without additional settings.

S-VIDEO IN Port


This is called super video. S-Video is a type of video signal which has the video luminance and the color signal separated in order to provide better visual quality.

VHF/UHF

VHF refers to TV channels 2 to 13, and UHF refers to TV channels 14 to 69.

Pixels, Resolution

The pixels are the number of small dots that make up the TV screen. The resolution represents the number of pixels on a screen. For example, if the resolution of a TV is 852x480, it means the width of the screen consists of 852 pixel columns and the height of the screen consists of 480 pixel rows. In this case, the total number of pixels on the screen is 408,960. The more pixels there are, the higher the visual quality that can be achieved because the picture on the screen is displayed with more pixels and therefore with more detail.



Gradation, Color Depth

Gradation describes the number of gradual brightness levels. Since all information is represented by binary numbers in a digital system, the Gradation is determined by the number of bits used to represent the brightness levels of a pixel on the TV screen. For example, if a pixel is represented by 8 bits, the Gradation is 28 or 256. Since a TV uses the three primary colors of light, R, G and B, the number of possible colors for a pixel is $256 \times 256 \times 256$, 16,777,216, or 16.7 million colors. If 12 bits are used for a pixel, the gradation is 212 or 4096 for a color. Since three colors R, G and B are used, $4096 \times 4096 \times 4096$ or 68.7 billion colors are supported per pixel. Since 68.7 billion colors are far more than 16.7 million colors, the picture will be displayed by far more abundant and natural colors using a 12 bit pixel. That is, since Gradation means the number of brightness levels, color represented by 4096 levels appears more natural than color represented by 256 levels.



Contrast

The contrast is the ratio of brightness of the brightest color to the darkest color. The contrast is calculated by dividing the brightness of the brightest color by the brightness of the darkest color. For example, if the brightness of the darkest color is 1 and the brightness of the brightest color is 3000, then the Contrast is $3000/1$ or 3000. A higher contrast means that a dark color is displayed darker and bright color is displayed brighter so that the screen contrast can be easily distinguished. The contrast differs from the Gradient which means the number of brightness levels.

Therefore, if someone says that a 5000:1 contrast displays a color by 5000 levels, he is confusing Contrast with Gradation.

Brightness

Brightness is the brightness per unit screen area, the unit for brightness is candela (cd). For example, 1000cd/m² means the brightness that is measured when 1000 candles are lit within 1 square meters area.

Color Reproductivity

Each color displayed on the TV screen is implemented by a pixel on color coordinates which have an X and Y axis.

For example, when a pixel on the X coordinate 0.65 and the Y coordinate 0.74 is displayed as a color and it becomes visible on the TV screen. While the possible color coordinate area is very wide, the color coordinate area of the signal broadcast from a broadcast station is smaller than that of possible color coordinates. Moreover, a TV provides a smaller color coordinate area than that of the signal from the broadcasting station even though the size of the color coordinate area varies depending on the TV model. In general, Color Reproductivity is used as follows:

The Color reproductivity of a TV is a certain % of NTSC. This means the TV displays that particular % of the color coordinate area of the NTSC signal broadcast by the broadcasting station. In general, a CRT TV provides the highest functional color reproductivity.

